



## NOKORODE® PASTE FLUXES

### Nokorode® Aqua Flux™

Code	Description	Qty.
74044	2 oz.	48
74047	4 oz.	24
74046	16 oz.	12



#### FEATURES

- Lead free
- Creamy, smooth paste
- Safe for potable water systems
- Certified to NSF/ANSI 61-G & 372
- Meets ASTM B-813 specs
- Complies with AB 1953 requirements

#### Water washable flux

#### Application

- Meets the ASTM B-813 standard requiring that flux residue shall be water flushable after soldering
- Superior wetting ability; Allows solder to flow easily and uniformly into joints
- Lead free joints

#### Recommended for

- Solid wire solders 95/5, 60/40, 50/50 and 40/60
- For use with the silicon family of metal alloy products



**NOKORODE® PASTE FLUXES**

Continued

**Nokorode® Regular**

Multi-purpose paste flux

Code	Description	Qty.
14000	1.7 oz.	48
14010	4 oz.	24
14020	8 oz. tool box	24
14030	1 lb.	12

**FEATURES**

- Lead Free
- Cleans & fluxes all at one time
- Safe for potable water systems
- Certified to NSF/ANSI 61-G & 372
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

**Application** • All purpose, soft soldering paste flux with a special oil base that protects the solder against corrosive attack

- Non-aggressive formula. Ideal for copper and brass fittings

**Recommended for**

- All solder alloys including 95/5 and lead free solders

**Nokorode® Hot Weather**

Does not liquefy in hot temperatures

Code	Description	Qty.
14800	1.7 oz.	48
14820	8 oz. tool box	24
14830	1 lb.	12

**FEATURES**

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

**Application** • Formulated to remain firm and stable in higher temperatures • Non-aggressive formula for use on copper and brass fittings

**Recommended for**

- All solder alloys including 95/5 and lead free solders

**Nokorode® Cold Weather**

Does not harden in cold temperatures

Code	Description	Qty.
14700	1.7 oz.	48
14720	8 oz.	24
14730	1 lb.	12

**FEATURES**

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

**Application** • Formulated to stay soft and sticky in cold weather • Low corrosivity, scorching and spattering. Works to deliver a strong, leak-free joint

**Recommended for**

- All solder alloys including 95/5 and lead free solders

