

No. 100 Virgin™

Industrial grade PTFE pipe thread sealant

Code	Description	Qty.
22631	¼ pt.	24
22551	½ pt.	24
22431	1 pt.	12
22390	1 qt.	12
22271	1 gal.	4
22191	5 gal.	1
22112	55 gal.	1



FEATURES

- Non-setting
- Lubricates & protects threads
- Lead free

Application • Non-hardening, industrial grade sealant containing virgin PTFE to provide maximum sealing performance
 • Can be pressurized immediately • Brushable from 20°F to 140°F

Recommended for • Galvanized Steel

- Iron • Brass • Copper
- Aluminum • Stainless Steel
- Polyethylene • RTRP
- PVC • CPVC • ABS



See ordering chart for container sizes available.

Blue+™

PTFE enriched non-setting pipe thread sealant

Code	Description	Qty.
31633	¼ pt.	24
31553	½ pt.	24
31433	1 pt.	12
31303	1 qt.	12



LISTED
PIPE JOINT
COMPOUND
MH12259

FEATURES

- Non-Setting
- Lead Free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

Application • Use on lines carrying potable water (hot or cold), DWV, natural gas, LPG, compressed air, and most other industrial gases. • Up to 10,000 psi liquid and 2,000 psi gases. • Temperature service range of -15°F to 350°F. • Not recommended for oxygen.

Recommended for • Galvanized Steel • Iron • Brass

- Stainless Steel • Copper • Aluminum • PVC
- CPVC • ABS • Polyethylene Reinforced Fiberglass

