

PULLOUT DISCONNECT SWITCHES

- Includes multiple knockouts on all enclosure sides
- Rainproof NEMA 3R outdoor enclosure



Pullout Disconnect Switches – Fused (Top Open)

PART NO	ENCL MATERIAL	DOOR STYLE	VOLTAGE (V)	CURRENT (A)	FUSING	CASE QTY	CASE REQ
84-25175-04	Steel	Top Open	230	30	Fused	10	Yes

Pullout Disconnect Switches – Non-Fused (Top Open)

PART NO	ENCL MATERIAL	DOOR STYLE	VOLTAGE (V)	CURRENT (A)	FUSING	CASE QTY	CASE REQ
84-25175-05	Steel	Top Open	230	60	Non-fused	10	Yes

HVAC WIRING WHIPS



HVAC Wiring Whips

PART NO	CONDUIT TRADE SIZE (IN)	CONDUIT LENGTH (FT)	CONDUCTOR LENGTH (IN)	POWER COND SIZE (AWG)	GROUND COND SIZE (AWG)	FITTING 1 TYPE	FITTING 2 TYPE	CASE QTY	CASE REQ
849039	1/2	4	68	10	10	Straight (Removable)	90° Elbow (Removable or Integral)	12	Yes
849040	1/2	6	92	10	10	Straight (Removable)	90° Elbow (Removable or Integral)	12	Yes
849041	3/4	4	70	8	10	Straight (Removable)	90° Elbow (Removable or Integral)	12	Yes
849042	3/4	6	94	8	10	Straight (Removable)	90° Elbow (Removable or Integral)	12	Yes

LIQUID-TIGHT CONDUIT



Liquid-Tight Conduit (Flexible Non-Metallic)

PART NO	DESCRIPTION
8431	Liquid-Tight Flexible Non-Metallic Conduit (1/2 in. x 100 ft.)
8432	Liquid-Tight Flexible Non-Metallic Conduit (3/4 in. x 100 ft.)
PD455009	Liquid-Tight Flexible Non-Metallic Conduit (1 in. x 100 ft.)

LIQUID-TIGHT CONDUIT FITTINGS



Liquid-Tight Conduit Fittings – Straight

PART NO	DESCRIPTION	CASE QTY	CASE REQ
455005	Liquid-Tight Conduit Fitting - 1/2 in. Straight	25	Yes
PD455007	Liquid-Tight Conduit Fitting - 3/4 in. Straight	10	Yes

Liquid-Tight Conduit Fittings – Straight (Quick Twist)

PART NO	DESCRIPTION	CASE QTY	CASE REQ
455001	Liquid-Tight Conduit Fitting - 1/2 in. Straight (Quick Twist)	25	Yes
455003	Liquid-Tight Conduit Fitting - 3/4 in. Straight (Quick Twist)	25	Yes