

S8610U3009

Universal Intermittent Pilot Control

Honeywell



The best keeps getting better. Improved performance in challenging applications, simplified diagnostic LED status and error codes, and direct flame current readout highlight the enhancements to the S8610U3009 Universal Intermittent Pilot Ignition Module. The S8610U offers replacement compatibility of more than 400 Honeywell and competitive models. This control is application flexible and works in both single and dual rod systems with Natural or LP gas, and features field selectable prepurge and ignition trial timings.

S8610U3009 Universal Intermittent Pilot Control



Suitable for use with or without vent dampers the S8610U provides the ignition sequence, flame monitoring and 100 percent safety shutoff for intermittent pilot central furnaces and heating appliances. Enhancements that improve the performance and simplify troubleshooting highlight the latest release of the Universal control.

IMPROVED PERFORMANCE

The S8610U has been enhanced resulting in improved performance in challenging applications and installations. The flame voltage auto-adjusts during operation ensuring maximum sensitivity during light-off and when flame strength is low while reducing sensitivity during normal operation. The result maximizes the opportunity to keep the appliance running during light-off and reducing the potential for flame rod contaminant attraction during normal operation.

Learn More

Call toll-free **1-800-328-5111**,
e-mail info@honeywell.com,
or visit forwardthinking.honeywell.com.

Automation and Control Solutions

In the U.S.:

Honeywell

1985 Douglas Drive North
Golden Valley, MN 55422-3992

In Canada:

Honeywell Limited

35 Dynamic Drive

Toronto, Ontario M1V 4Z9

www.honeywell.com

Spark voltage and spark duty cycle have both been modified to ensure a faster and more consistent light-off. The spark voltage stays constant even if the input voltage varies allowing for a more consistent light-off. Spark duty cycle has increased to 90% allowing for a faster light-off while still allowing adequate time to sense and prove flame.

SIMPLIFIED TROUBLESHOOTING

A single LED is utilized to display the device status, error codes and flame strength. Error and status codes are clearly displayed on the product label for easy identification. Technicians now have the ability to receive flame current readout with a standard micro-ammeter through contact holes provided on the board. All of these improvements allow technicians to more quickly diagnose problems, take corrective action and get on to their next job.

UNIVERSAL APPLICATION

With a cross reference of more than 400 Honeywell and competitive models the S8610U ensures your technicians are prepared to fix it right the first time and keep that truck on the job and not waiting for parts.

Honeywell