



# PACKAGE AIR CONDITIONERS

FORM NO. EXA11-186 REV. 1  
Supersedes Form No. EXA11-186

**SSNM- HIGH EFFICIENCY –  
50 Hz – EXPORT AIR CONDITIONER  
NOMINAL SIZES 2, 3-6 TON [7, 10.6-21.1 kW]  
R-410A Refrigerant**

**R-410A**





**220/240 VOLT, THREE PHASE, 60 HZ, AUXILIARY ELECTRIC HEATER KITS CHARACTERISTICS AND APPLICATION**

Single Power Supply For Both Unit and Heater Kit										Separate Power Supply For Both Unit and Heater Kit						
Model No. SSNM-	Heater Kit					Air Conditioner					Heater Kit			Air Conditioner		
	RXQJ- Heater Kit Nominal kW	No. of Sequence Steps	Rated Heater kW @ 220/240 V	Heater KBTU/Hr @ 220/240 V	Heater Amp. @ 220/240 V	Unit Min. Ampacity @ 220/240 V	Over Current Protective Device Size		Min. Ckt. Ampacity 220/240V	Max. Fuse Size 220/240V	Min. Circuit Ampacity 220/240 V	Over Current Protective Device Size				
							Min./Max. @ 208 V	Min./Max. @ 240 V				Min./Max. @ 208 V	Min./Max. @ 240 V			
A024TK	No Heat	—	—	—	—	15/15	20/20	20/20	—	15/15	20/20	20/20	20/20			
	C05J	1	4/4.8	13.73/16.38	18.3/20	25/27	25/25	30/30	23/25	—	—	—	—			
	C07J	1	6.1/7.2	20.64/24.56	27.5/30	37/40	40/40	40/40	35/38	—	—	—	—			
A036TK	C10J	1	8.1/9.6	27.55/32.75	36.7/40	48/52	50/50	60/60	46/50	—	—	—	—			
	No Heat	—	—	—	—	21/21	25/30	25/30	—	21/21	25/30	25/30	25/30			
	C05J	1	4/4.8	13.73/16.38	18.3/20	26/29	30/30	30/30	23/25	—	—	—	—			
	C07J	1	6.1/7.2	20.64/24.56	27.5/30	38/41	40/40	45/45	35/38	—	—	—	—			
A048TK	C10J	1	8.1/9.6	27.55/32.75	36.7/40	50/54	50/50	60/60	46/50	—	—	—	—			
	C15J	1	12.1/14.4	41.28/49.13	55/60	72/79	80/80	80/80	69/75	—	—	—	—			
	No Heat	—	—	—	—	28/28	35/45	35/45	—	28/28	35/45	35/45	35/45			
	C05J	1	4/4.8	13.73/16.38	18.3/20	28/30	35/45	35/45	23/25	—	—	—	—			
	C07J	1	6.1/7.2	20.64/24.56	27.5/30	39/42	40/45	45/45	35/38	—	—	—	—			

**380/415 VOLT, THREE PHASE, 60 HZ, AUXILIARY ELECTRIC HEATER KITS CHARACTERISTICS AND APPLICATION**

Single Power Supply For Both Unit and Heater Kit										Separate Power Supply For Both Unit and Heater Kit						
Model No. SSNM-	Heater Kit					Air Conditioner					Heater Kit			Air Conditioner		
	RXQJ- Heater Kit Nominal kW	No. of Sequence Steps	Rated Heater kW @ 380/415 V	Heater KBTU/Hr @ 380/415 V	Heater Amp. @ 380/415 V	Unit Min. Ampacity @ 380/415 V	Over Current Protective Device Size		Min. Ckt. Ampacity 380/415V	Max. Fuse Size 380/415V	Min. Circuit Ampacity 380/415 V	Over Current Protective Device Size				
							Min./Max. @ 208 V	Min./Max. @ 240 V				Min./Max. @ 208 V	Min./Max. @ 240 V			
A042NK	No Heat	—	—	—	—	10/10	15/15	15/15	—	10/10	15/15	15/15	15/15			
	A048NK	—	—	—	—	11/11	15/15	15/15	—	—	—	—	—			
	A060NK	—	—	—	—	14/14	20/20	20/20	—	—	—	—	—			
A072NK	—	—	—	—	—	18/18	25/25	25/25	—	—	—	—	—			