


# SERIES 41 MANIFOLDS

°F and °C with 2-1/2" (63.5 mm) gauges



Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

- Flutterless™ technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings
- Sliding double “O” ring pistons reduces wear
- Most manifolds include color-coded YELLOW JACKET charging hoses
- Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B)
- Limited lifetime warranty on manifold bar and valves – not gauges. See warranty information for details
- Made in the USA 



Series 41 Manifolds				
UPC#	Description - °F and °C - Red/Blue	Scale	Refrigerant	
42051	Heat pump manifold only, 1/4-5/16-1/4"	bar/psi	R-410A	
42054	With 60" black PLUS II hoses (two 1/4x5/16" ball valve and one 1/4x1/4" ball valve)	bar/psi		
41712	Manifold only	kg/cm <sup>2</sup> /psi	R-410A	
41703	With 60" PLUS II™ compact ball valve fittings	kg/cm <sup>2</sup> /psi		
41709	With 60" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi		
41715*	With 60" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi		
41710	With 60" PLUS II™ heavy duty black standard fittings	kg/cm <sup>2</sup> /psi		
41702	With 60" PLUS II™ heavy duty black compact ball valve fittings	kg/cm <sup>2</sup> /psi		
42715	With 60" PLUS II™ compact ball valve fittings	kg/cm <sup>2</sup> /psi		
41711*	With 60" PLUS II™ compact ball valve fittings	kg/cm <sup>2</sup> /psi		
41652	Manifold only with 5/16, 1/4", 5/16" hose fittings	bar/psi	R-32/410A	
UPC#	Description - °F - Red/Blue	Scale	Refrigerant	
41212	Manifold only	psi	R-12/22/502	
41213	With 36" PLUS II™ standard fittings	psi		
41220	With 48" PLUS II™ standard fittings	psi		
41215	With 60" PLUS II™ standard fittings	psi		
41219	With 72" PLUS II™ standard fittings	psi		
44213	With 36" PLUS II™ SealRight fittings	psi		
44220	With 48" PLUS II™ SealRight fittings	psi		
44215	With 60" PLUS II™ SealRight fittings	psi		
44219	With 72" PLUS II™ SealRight fittings	psi		
42215	With 60" PLUS II™ compact ball valve fittings	psi		
42219	With 72" PLUS II™ compact ball valve fittings	psi		
41312	Manifold only	psi	R-134a/404A/507	
41313	With 36" PLUS II™ standard fittings	psi		
41311	With 48" PLUS II™ standard fittings	psi		
41315	With 60" PLUS II™ standard fittings	psi		
41319	With 72" PLUS II™ standard fittings	psi		
43313	With 36" PLUS II™ standard fittings	psi		
44313	With 36" PLUS II™ SealRight fittings	psi		
44315	With 60" PLUS II™ SealRight fittings	psi		
44319	With 72" PLUS II™ SealRight fittings	psi		
42315	With 60" PLUS II™ compact ball valve fittings	psi		
41202	Manifold only	psi	R-22/134a/404A	
41209	With 36" PLUS II™ standard fittings	psi		
41211	With 60" PLUS II™ standard fittings	psi		
UPC#	UPC#	Description - °C - Red/Blue	Scale	Refrigerant
42008		Manifold only	bar/psi	R-12/22/502
41283		With 36" PLUS II™ standard fittings	bar/psi	
41285		With 60" PLUS II™ standard fittings	bar/psi	
42002		Manifold only	kPa/psi	
41223		With 36" PLUS II™ standard fittings	kPa/psi	
41225		With 60" PLUS II™ standard fittings	kPa/psi	
41292		Manifold only	kg/cm <sup>2</sup> /psi	
41293		With 36" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
41295		With 60" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
41299		With 72" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
41382		Manifold only	bar/psi	R-134a/404A/507
41353		With 36" PLUS II™ standard fittings	bar/psi	
41355		With 60" PLUS II™ standard fittings	bar/psi	
43355		With 60" PLUS II™ standard fittings	bar/psi	
41392		Manifold only	kg/cm <sup>2</sup> /psi	
41363		With 36" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
41365		With 60" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
43365		With 60" PLUS II™ standard fittings	kg/cm <sup>2</sup> /psi	
41332		Manifold only	bar/psi	R-134a/404A/407C
40944		Manifold only with 1/4" ports and 5/16" hose fittings	bar/MPa	R-410A
41781		Manifold only with 5/16" fittings	bar/MPa	
41780		Manifold only with 1/4" fittings	bar/MPa	

\*Special R-410A hose - R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.

RECOVERY MACHINES  
 VACUUM PUMP SYSTEMS  
 VACUUM AND CHARGING HOSES  
 HOSE ADAPTERS, VALVES AND PARTS  
 CHARGING SYSTEMS  
 GAUGES  
 WIRELESS AND ELECTRONIC INSTRUMENTS  
 HEATING INSTRUMENTS  
 LEAK MONITORS AND DETECTORS  
 SYSTEM TOOLS