SERIES 41 MANIFOLDS

°F and °C with 3-1/8" (80 mm) gauges



Series 41 manifolds are also available with larger, easier to read 3-1/8" color-coded gauges in rugged steel cases with polycarbonate crystals. These gauges feature 1% accuracy (Class 1) for an exact reading in critical charge systems.

- Color-coded scales
- Sliding double "O" ring pistons reduce wear
- Long life nylon seats
- Forged brass body for durability
- · Full porting maximizes capacity and flow
- Some models include color-coded, 60" PLUS II™ hoses with standard 1/4" flare fittings
- Hose assemblies UL recognized for 4000 psi (275) bar) burst and 800 psi (55 bar) working pressure. File# SA9737
- Made in the USA



• Made in the USA						
Box	Clamshell	nell				
UPC#	UPC#	Description - °F/°C	Scale	Refrigerant		
41863	-	Manifold only with 5/16"-1/4"-5/16" anchor fittings and 1/4" service fittings - red/blue gauge	kPa/psi			
41652	-	Manifold only with 5/16", 1/4", 5/16" anchor and 1/4" service fittings	bar/psi			
41659 -	- 42021 42024	Manifold only with 5/16" anchor fittings Manifold only With 60" <i>PLUS II</i> ™ standard fittings	bar/psi bar/psi bar/psi	R-32/410A		
41862	-	Manifold only with 5/16" anchor and service fittings	kPa/psi			
-	41865	41862 with 60" <i>PLUS II</i> ™ 5/16" fittings	kPa/psi			
	41866	Manifold only	bar/kPa/psi	R-600		
UPC#	UPC#	Description - °F - Red/Blue	Scale	Refrigerant		
-	41842	Manifold only	psi			
-	42007	With 60" PLUS II [™] standard fittings	psi	R-12/22/134a		
-	41846	With 72" PLUS II™ with couplers	psi			
_	42001	Manifold only	psi			
-	49271*	Certified 42001 manifold		D 00/4044/4404		
_	42004 42201	With 60" PLUS II™ standard fittings	psi	R-22/404A/410A		
_	42005	With 60" <i>PLUS II</i> [™] compact ball valve fittings Manifold only	psi psi			
_	49272*	Certified 42005 manifold	poi			
_	42006	With 60" <i>PLUS II</i> ™ standard fittings	psi	R-22/134a/404A		
_	42205	With 60" <i>PLUS II</i> [™] compact ball valve fittings	psi			
UPC#	UPC#	Description - °C - Red/Blue	Scale	Refrigerant		
_	41622	Manifold only	bar/psi			
-	41852	Manifold only	kPa/psi	R-22/134a/404A		
-	41855	With 60" PLUS II™ standard fittings	kPa/psi			
-	41632	Manifold only	bar/psi	R-12/134a/413A		
-	42031	Manifold only	psi	R-22/404A/410A		
41784	42034	With 60" PLUS II™ hose, standard fittings Manifold only with 5/16" fittings	MPa	R-32/410A		
		mamora orn, mar o, ro mango	0	02/0/ (

SERIES 41 DELUXE **MANIFOLDS**

°F Class 1 (1% accuracy) brass gauges



All the same features as the regular "Series 41" with 1% accuracy (Class 1) brass gauges.

- Upgraded movement with phosphor bronze plates, brass gears and pinions. Dissimilar parts create less friction and last longer. FlutterLess™ technology included
- · Polished solid brass case with glass crystals
- Made in the USA

UPC#	Description	Scale	Refrigerant
44235	With 60" <i>PLUS II</i> ™ SealRight fittings	psi	R-12/22/502
42332	Manifold only	psi	
42333	With 36" PLUS II™ compact ball valve fittings	psi	
42436	With 60" <i>PLUS II</i> ™ compact ball valve fittings	psi	R-22/134a/ 404A
42435	With 60" <i>PLUS II</i> [™] standard fittings	psi	
45221	Retro manifold °C	psi	R-134a/404A 407C
45222	Retro manifold °F	psi	

Manifold comes standard with certified gauges. For more information on the certification of 3-1/8" gauges, see page 51.

NH₃ AMMONIA MANIFOLD

UPC#	Description
40190	Manifold body with valves
40192	Manifold and gauges
40193	Manifold and gauges with three NHA 48" hoses
40199	Replacement valve assembly
41131	"O"-rings (10 pak)
41142	Replacement screw
41151	Hose anchor

This heavy duty manifold features cast iron body and full size metal handles. Dual temperature/pressure R717 gauge has bar with °C and psi with °F ammonia scales.

- Finger-tight one-piece valve stem for positive seal on nylon seat
- Easy, accurate valve adjustment
- Use only with NH₃ rated hoses
- Made in the USA

