

Commander Exposed Shower

FEATURES:

- Commander exposed shower on 6 in. centers
- ¼ turn ceramic cartridges
- Chrome plated patented vandal-resistant four arm handles with color-coded indexes
- Reversible valve body
- S-2272-E2 showerhead with 2.0 gpm (7.57 L/min) flow rate
- Exposed chrome plated shower body assembly
- 1/2 in. NPTM chrome plated brass riser supply pipes
- Polished chrome plated brass gooseneck with supporting strap

FINISH:



PC

COMPLIANCE:

- ASME A112.18.1/CSA B125.1 standard
- WaterSense certified (S-2272-E2 shower head)

OPTIONS:

Add suffix to model #

- | | |
|---------------------|-------------------------------|
| • Less showerhead | <input type="checkbox"/> -LH |
| • Less supply pipes | <input type="checkbox"/> -LSP |
| • S-2251 showerhead | <input type="checkbox"/> -1 |
| • S-2252 showerhead | <input type="checkbox"/> -2 |
| • S-2253 showerhead | <input type="checkbox"/> -3 |
| • S-2292 showerhead | <input type="checkbox"/> -9 |

WARRANTY:

- 1 year limited (shower head)
- 5 year limited



DIMENSIONS: NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified, all inlets and outlets are 1/2" male NPT threads.

