




CTS CPVC Technical
CTS Product Dimensions

90° EII


Socket x Socket
NSF® Certified Lead Free



Part Number	Size	G	H	M	Approx. Wt. (Lbs.)
4106-005	1/2	13/32	15/16	27/32	.02
4106-007	3/4	17/32	1- 1/4	1- 1/8	.04
4106-010	1	21/32	1- 9/16	1- 3/8	.07
4106-012	1-1/4	3/4	1- 7/8	1-11/16	.12
4106-015	1-1/2	29/32	2- 7/32	2	.21
4106-020	2	1- 5/32	2- 7/8	2-19/32	.46

90° EII - Reducing

Socket x Socket
NSF® Certified Lead Free



Part Number	Size	G	G1	H	H1	M	M1	Approx. Wt. (Lbs.)
4106-101	3/4X1/2	3/8	1/2	1- 3/32	1- 1/32	1- 3/32	27/32	.03
4106-130 ¹	1X1/2	11/16	1-9/32	1-19/32	1-13/16	1-3/8	1-3/8	.11
4106-131 ¹	1X3/4	21/32	1	1- 9/16	1- 3/8	1- 3/8	1- 3/8	.10
4106-167 ¹	1-1/4X3/4	13/16	1- 1/2	1-29/32	2- 7/32	1-21/32	1-21/32	.19
4106-168 ¹	1-1/4X1	13/16	1- 5/16	1-29/32	2- 7/32	1-21/32	1-21/32	.17
4106-209 ¹	1-1/2X1/2	15/16	2- 1/32	2- 1/4	2-17/32	1-31/32	1-31/32	.32
4106-210 ¹	1-1/2X3/4	15/16	1-27/32	2- 1/4	2- 9/16	1-31/32	1-31/32	.31
4106-211 ¹	1-1/2X1	15/16	1-21/32	2- 1/4	2-19/32	1-31/32	1-31/32	.31
4106-212 ¹	1-1/2X1-1/4	15/16	1-13/32	2- 1/4	2-17/32	1-31/32	1-31/32	.27
4106-247 ¹	2X1/2	1- 3/16	2-11/16	2-29/32	3- 3/16	2- 9/16	2- 9/16	.66
4106-248 ¹	2X3/4	1- 3/16	2- 7/16	2-29/32	3- 5/32	2- 9/16	2- 9/16	.67
4106-249 ¹	2X1	1- 3/16	2- 9/32	2-29/32	3- 3/16	2- 9/16	2- 9/16	.68
4106-250 ¹	2X1-1/4	1- 3/16	2- 1/16	2-29/32	3- 5/32	2- 9/16	2- 9/16	.66
4106-251 ¹	2X1-1/2	1- 3/16	1-29/32	2-29/32	3- 7/32	2- 9/16	2- 9/16	.64

¹ Outlet sized with bushing.