


Schedule 80 CPVC Technical
Schedule 80 CPVC Pipe Dimensions & Pressure Ratings



Pipe - CPVC Schedule 80 Plain End

(Continued)


10' Lengths



| Part Number | Size | L | AVG.O.D. | Minimum Wall | Approx. Wt. (Lbs./Ft) |
|----------------|------|----|----------|--------------|-----------------------|
| PD-800-180C-10 | 18 | 10 | 18 | .970 | 35.41 |
| PD-800-200C-10 | 20 | 10 | 20 | 1.031 | 45.87 |
| PD-800-240C-10 | 24 | 10 | 24 | 1.218 | 64.95 |

Pipe - CPVC Schedule 80 Plain End

20' Lengths



| Part Number | Size | L | AVG.O.D. | Minimum Wall | Approx. Wt. (Lbs./Ft) |
|-------------|-------|----|----------|--------------|-----------------------|
| PD-800-001C | 1/8 | 20 | .405 | .095 | .10 |
| PD-800-002C | 1/4 | 20 | .540 | .119 | .11 |
| PD-800-003C | 3/8 | 20 | .675 | .126 | .16 |
| PD-800-005C | 1/2 | 20 | .840 | .147 | .22 |
| PD-800-007C | 3/4 | 20 | 1.050 | .154 | .30 |
| PD-800-010C | 1 | 20 | 1.315 | .179 | .44 |
| PD-800-012C | 1-1/4 | 20 | 1.660 | .191 | .61 |
| PD-800-015C | 1-1/2 | 20 | 1.900 | .200 | .75 |
| PD-800-020C | 2 | 20 | 2.375 | .218 | 1.03 |
| PD-800-025C | 2-1/2 | 20 | 2.875 | .276 | 1.58 |
| PD-800-030C | 3 | 20 | 3.500 | .300 | 2.12 |
| PD-800-040C | 4 | 20 | 4.500 | .337 | 3.10 |
| PD-800-050C | 5 | 20 | 5.563 | .375 | 4.55 |
| PD-800-060C | 6 | 20 | 6.625 | .432 | 5.92 |
| PD-800-080C | 8 | 20 | 8.625 | .500 | 9.04 |
| PD-800-100C | 10 | 20 | 10.750 | .593 | 13.01 |
| PD-800-120C | 12 | 20 | 12.750 | .687 | 18.35 |
| PD-800-140C | 14 | 20 | 14 | .750 | 23.25 |
| PD-800-160C | 16 | 20 | 16 | .843 | 29.89 |
| PD-800-180C | 18 | 20 | 18 | .970 | 35.42 |
| PD-800-200C | 20 | 20 | 20 | 1.031 | 45.87 |
| PD-800-240C | 24 | 20 | 24 | 1.218 | 64.95 |