

Low-Watt Density Screw-In Elements

BEST Low-Watt Density Elements- Incoloy Nickel Base

| Part Number | NEW Part Number | Volts | Watts | "A" Dim. Inches |
|-------------|-----------------|-------|-------|-----------------|
| 9004279115 | 100109745 | 120 | 1500 | 9 |
| 9004284115 | 100109751 | 208 | 2000 | 9 |
| 9004753115 | 100110061 | 208 | 5000 | 16.5 |
| 9004289115 | 100109756 | 208 | 6000 | 16.5 |
| 9004290115 | 100109758 | 240 | 1500 | 9 |
| 9004283115 | 100109750 | 240 | 2000 | 11.5 |
| 9004291115 | 100109759 | 240 | 2500 | 11 |
| 9000664015 | 100108440 | 240 | 3000 | 13.5 |
| 9004292115 | 100109761 | 240 | 3500 | 13.75 |
| 9000225015 | 100108346 | 240 | 3800 | 14 |
| 9004751115 | 100110060 | 240 | 4000 | 16 |
| 9003210115 | 100109139 | 240 | 4500 | 13.75 |
| 9004294115 | 100109765 | 240 | 5500 | 13.5 |
| 9004293115 | 100109763 | 240 | 5000 | 16 |
| 9004749115 | 100110058 | 240 | 6000 | 16.5 |
| 9004296115 | 100109768 | 277 | 3000 | 16.5 |
| 9004297115 | 100109770 | 277 | 4500 | 16.5 |
| 9004298115 | 100109772 | 480 | 2000 | 16 |
| 9004300005 | 100109774 | 480 | 3000 | 16.5 |
| 9004763105 | 100110069 | 480 | 4000 | 16.5 |
| 9004760115 | 100110066 | 480 | 4500 | 16.5 |
| 9004761105 | 100110067 | 480 | 5000 | 16.5 |
| 9004762105 | 100110068 | 480 | 6000 | 16.5 |

FEATURES & BENEFITS OF LOW-WATT DENSITY ELEMENTS

- Nickel-alloy stainless steel sheath
- Long lasting, lowest practical watt density
- Includes Gasket
- Screw-In Element, industry standard 1" NPSM thread



BETTER 1-3/8" Screw-In Flange

| Part Number | NEW Part Number | Volts | KW | "A" Dim. Inches |
|-------------|-----------------|-------|------|-----------------|
| 9002451015 | 100108813 | 240 | 3000 | 14 |
| 9002434015 | 100108796 | 240 | 3800 | 14 |
| 9002449015 | 100108810 | 240 | 3800 | 14 |
| 9002441015 | 100108801 | 240 | 3000 | 14 |
| 9002448015 | 100108809 | 240 | 5500 | 14 |
| 9002442015 | 100108803 | 240 | 4500 | 14 |

