

The Stinger HPL is a long-range, hand-held flashlight that produces a wide, 800 lumen beam pattern with brighter peripheral illumination and superior down-range performance.



|  |
|--|
| <p>Four operating modes:</p> <ul style="list-style-type: none"> <li>- High for a high lumen, far-reaching beam: 800 lumens; 438m beam distance; 48,000 candela; runs 1.5 hours</li> <li>- Medium for bright light and longer run time: 400 lumens; 310m beam distance; 24,000 candela; runs 2.5 hours</li> <li>- Low provides a less intense beam and extended run time: 200 lumens; 219m beam distance; 12,000 candela; runs 5 hours</li> <li>- Strobe for disorienting or signaling: runs 3 hours</li> </ul> |
| <p>Optimized electronics provide regulated intensity</p>   |

|  |
|--|
| <p>IPX4 water resistant<br/>         3 meter impact resistance tested</p>  |
| <p>Serialized for positive identification</p>  |
| <p>Stinger HPL: 9.23 in. (23.44 cm); 13.6 oz (385 grams)<br/>         Stinger DS HPL: 9.65 in. (24.51 cm); 14.0 oz (396 grams)</p>             |
| <p>Limited Lifetime Warranty<br/>         Visit <a href="http://www.streamlight.com">www.streamlight.com</a> for full warranty information</p> |
| <p>See reverse for system configurations</p>   |

| Item #                | Item Description  |
|-----------------------|---|
| <b>Stinger HPL</b>    |   |
| 75982                 | Stinger HPL - IEC Type C (230V) AC/12V DC (NiMH)                        |
| 75779                 | Stinger HPL - IEC Type G (240V) AC/12V DC (NiMH)                        |
| 75763                 | Stinger HPL - IEC Type A (120V) AC/12V DC Smart Charge (NiMH)           |
| 75758                 | Stinger HPL - IEC Type A (100V) AC/12V DC (NiMH)                        |
| 75981                 | Stinger HPL - IEC Type C (230V) AC(NiMH)                                |
| 75778                 | Stinger HPL - IEC Type G (240V) AC (NiMH)                               |
| 75761                 | Stinger HPL - IEC Type A (120V) AC Smart Charge (NiMH)                  |
| 75757                 | Stinger HPL - IEC Type A (100V) AC (NiMH)                               |
| 75799                 | Stinger HPL - 12V DC (NiMH)   |
| 75782                 | Stinger HPL - IEC Type A (120V) AC/12V DC PiggyBack Smart Charge (NiMH) |
| 75980                 | Stinger HPL (WITHOUT CHARGER) (NiMH)                                    |
| <b>Stinger DS HPL</b> |   |
| 75918                 | Stinger DS HPL - IEC Type C (230V) AC/12V DC SC (NiMH)                  |
| 75879                 | Stinger DS HPL - IEC Type G (240V) AC/12V DC SC (NiMH)                  |
| 75863                 | Stinger DS HPL - IEC Type A (120V) AC/12V DC Smart Charge (NiMH)        |
| 75858                 | Stinger DS HPL - IEC Type A (100V) AC/12V DC (NiMH)                     |
| 75916                 | Stinger DS HPL - IEC Type C (230V) AC(NiMH)                             |
| 75878                 | Stinger DS HPL - IEC Type G (240V) AC (NiMH)                            |
| 75861                 | Stinger DS HPL - IEC Type A (120V) AC Smart Charge (NiMH)               |
| 75857                 | Stinger DS HPL - IEC Type A (100V) AC (NiMH)                            |
| 75899                 | Stinger DS HPL - 12V DC Smart Charge (NiMH)                             |
| 75882                 | Stinger DS HPL - 120V AC/12V DC Smart Charge PiggyBack (NiMH)           |
| 75900                 | Stinger DS HPL - (WITHOUT CHARGER) (NiMH)                               |

