
METAL TUBING

HI-DUTY® TUBE CUTTERS

For 1/8" to 1-1/8" and 1/4" to 1-5/8" 0.D. tubing.

- Enclosed hardened steel, thrust bearing feed mechanism for smoothest cutting action and trouble free operation.
- Unique design eliminates spiraling for clean right angle cuts. Our high precision machining and construction method permits one-piece screw-type axle for easy access to cutter wheel — no clip to lose or replace.
- Rugged aluminum alloy body designed for handling ease. Body is hand buffed and nickel chrome plated to a high-luster finish.
- Foldaway hardened steel reamer with turned cutting edge removes inside burrs cleanly. Filing surface removes outside burrs.
- Rollers feature flare cut-off groove to reduce tube loss when damaged flare is removed.
- Imperial® cutter wheels are made of the highest quality wear and abrasion-resistant chromium steel and precision machined to exacting specifications for accurate cutting and long life. Each tool is supplied with a spare cutter wheel.
- All Imperial tube cutters are 100% factory tested to ensure accurate spiral-free cutting.



TC-1010 For 1/8" to 1-1/8" (4 mm to 28 mm) 0.D. tubing. Includes (2) S75046 cutter wheels for continuous cutting of stainless steel, monel and other hard-temper tubing. Length 5". Wt. 8.8 oz.

TC-1020 Combination tube constrictor & tube cutter. For 1/8" to 1-1/8" (4 mm to 28 mm) O.D. tubing. Includes S76637 constrictor wheel and S75015 general purpose cutter wheel. Length 5-1/2". Wt. 8.8 oz.

312-FC For 1/4" to 1-5/8" (7 mm to 41 mm) 0.D. tubing. Includes (2) S75015 general purpose cutter wheels. Length 5-1/2". Wt. 10.4 oz.

Conforms to Federal Specification GGG-C-771d, Type II, Class I.

S75015 General purpose cutter wheel.

S75046 Wheel for continuous cutting of stainless steel, monel and other hard temper tubing. For cutters TC-1000, TC-1010, TC-1550, TC-1560, 312-FC, 174-F, TC-2050 and TC-3050.

\$16003162 Replacement cutter wheel for soft copper & aluminum tubing is extra sharp to minimize burr buildup.

S76637 Constrictor wheel for producing sweat joints.






TC-1000











JUNIOR TUBE CUTTER

For 1/8" to 3/4" (4 mm to 19 mm) 0.D. tubing.

Includes S32633 general purpose cutter wheel. Swing radius 2". 227-FA Length 3-1/2". Wt. 5.0 oz.



METAL TUBING

For 1/8" to 5/8", 3/16" to 7/8" and 1/8" to 1-1/8" 0.D. tubing.

- Big capacity, small size tube cutters designed for use in tight quarters where other cutters won't fit.
- Enclosed feed screw minimizes contamination assuring continued smooth operation.
- Corrosion-resistant steel rollers positioned at bottom of cutter allow for easier cutter engagement on tubing and smoother cutting action.
- All Imperial® tube cutters are 100% factory tested to ensure accurate spiral-free cutting.

TC-1050 For 1/8" to 5/8" (4 mm to 15 mm) 0.D. tubing. Includes (1) S32633 general purpose cutter wheel. Swing radius 1-1/4" (1-3/8" swing radius

with 5/8" tube). Length 1-3/4". Wt. 2.5 oz.

S32633 General purpose cutter wheel for TC-1050.

S26883 Screw for TC-1050 cutter wheel.

TC-2050 For 3/16" to 7/8" (5 mm to 22 mm) 0.D. tubing. Includes (1) \$75015

general purpose cutter wheel. Swing radius 1-11/16".

Length 2-1/4". Wt. 4.0 oz.

TC-3050 For 1/8" to 1–1/8" (4 mm to 28 mm) 0.D. tubing. Includes (1) \$75015

general purpose cutter wheel. Swing radius 2-1/2" (2-1/16" swing radius

with 1-1/8" tube). Length 3". Wt. 7.0 oz.

General purpose cutter wheel. S75015

S74762

RATCHETING TUBE CUTTERS

For 1/8" to 5/8" and 1/8" to 1-1/8" 0.D. tubing.

• Easily completes a full revolution, maximizing leverage.

Screw for TC-3050 cutter wheel.

- Cutter can easily be removed from the handle.
- Ergonomic handle with non-slip grip.
- Six independent drive pawls provide 15° arc-swing.
- Includes (1) general purpose cutter wheel.

TC-1050RH For 1/8" to 5/8" (4 mm to 15 mm) 0.D. tubing.

2-Pc. set includes TC-1050"IMP"® mini tube cutter and ratcheting handle in clamshell packaging. Length 5". Wt. 6.0 oz.

TC-1051 Ratcheting handle only. Length 5". Wt. 1.5 oz.

TC-3050RH For 1/8" to 1-1/8" (4 mm to 28 mm) 0.D. tubing.

3-Pc. set includes TC-3050"IMP"® tube cutter, removable deburr tool and ratcheting handle in clamshell

packaging. Length 7". Wt. 11.5 oz.

Ratcheting handle and deburr tool. Length 7". Wt. 4.0 oz. TC-3051







TC-2050



1-11/16"

TC-3050

Use cutter with or without patented ratcheting handle snaps into place in seconds

TC-3050RH includes a removable deburr tool






Six independent drive pawls give small, 15° arc-swing



BIG "IMP" TUBE CUTTER - "Big capacity in small size" For 3/8" to 1-1/8" (10 mm to 28 mm) 0.D. tubing.

174-F Includes (2) S75015 general purpose cutter wheels. Swing radius 1-15/16" (2-1/4" swing radius with 1-1/8" tube). Length 2-11/16". Wt. 5.0 oz.



S75015 - Spare cutting wheel

METAL TUBING

ADJUST-O-MATIC™ TUBE CUTTERS

For 3/8" to 2-5/8" and 2" to 4-1/8" 0.D. tubing.

- Ratchet feed mechanism speeds up cutting operation.
- Extra wide rollers with flare cut-off groove stabilize tubing.
- Spare cutting wheel included under handle cap.
- Enclosed screw-type feed mechanism; lightweight aluminum alloy body.

206-FB For 3/8" to 2-5/8" (10 mm to 66 mm) 0.D. tubing. Includes (2) 574761 general purpose cutter wheels. Length closed 7-3/4". Wt. 2.0 lbs.

406-FA For 2" to 4-1/8" (51 mm to 104 mm) 0.D. tubing. Includes (2) \$74833

general purpose cutter wheels. Length closed 11-1/4". Wt. 3.5 lbs.

Conforms to Federal Specification GGG-C-771d, Type II, Class I.








RATCHET FEEDPush on handle to slide cutter wheel to tubing. Rotate handle for fine adjustment.



FLARE CUT-OFF GROOVE
Wide flare cut-off groove in rollers to accommodate flares on large size tubing.



144-F IMPERIAL® TUBE CUTTER SERVICE CENTER For 1/8" to 4-1/8" 0.D. tubing.

Selling Imperial® replacement cutter wheels, reamer blades and fasteners is easy. Our Service Center organizes a popular selection of replacement parts for Imperial cutters. Display on the counter or bring it with you when making sales calls.

- 15 most common replacement parts stocked in one handy container.
- Includes a visual replacement chart for quick and easy identification.

144-F SERVICE CENTER INCLUDES:

