


NS2000031 UNIVERSAL AIR PRESSURE SWITCH

Low Cost, High Accuracy and Reliable Universal Air Pressure Switch that Replaces Many Small Footprint Type Switches



- Senses Positive, Negative or Differential Air Pressure
- Set Point Range: .10" to 10"
- Electrical Ratings: 1/10 hp @ 120 to 277 VAC.
28 VA Pilot Duty @ 24 VAC,
125 VA Pilot Duty 120 VAC
- Contact Arrangement: SPDT
- Operating Temperature:
-40°F to 190°F (-40°C to 88°C)
- UL® & CSA® Approved
- 2-Year Warranty

ADJUSTABLE STYLE RSS SERIES AIR PRESSURE SWITCHES

Ideal for Residential and Light Commercial Furnace, Electronic Air Cleaner and Humidifier Applications.



- Convenient Contractor Kits for After-Market Installation
- Adjustable Set Points
- Factory Set to Activate on Pressure Rise
- Electrical Ratings: 5 Amp Non-inductive
120 to 277 VAC 1 Amp Pilot Duty (120 va) @ 120 VAC
- Contact Arrangement: SPDT
- Operating Temperature Range: -40°F to 190°F
(-40°C to 88°C)
- UL® & CSA® Approved
- 2-Year Warranty

Part No.	Range (In. of Water Column)
RSS495011	0.25" to 1.0"
RSS498013	1.0" to 4.0"

AFS222121 ADJUSTABLE STYLE AIR PRESSURE SWITCH

General Purpose Switch for HVAC, Direct Digital Control (DDC) and Energy Management Applications



- Senses Positive, Negative or Differential Air Pressure
- Set Point Range: 0.05" to 12.0" w.c.
- Electrical Ratings: 300 VA Pilot Duty
@ 115 to 277 VAC, 15 Amp Non-inductive
to 277 VAC, 60 Hz.
- Contact Arrangement: SPDT
- Operating Temperature: -40°F to 180°F
(-40°C to 82°C)
- UL® & CSA® Approved
- 2-Year Warranty

AIR PRESSURE SWITCH CROSS REFERENCE

SUPCO® Part No.	Competitor Name	Competitor Part No.
RSS495011	Robertshaw®	2374-495
RSS498013	Robertshaw®	2374-498
AFS222121	Robertshaw® White Rodgers®	2374-410 770-1
NS2000031	Honeywell®	IS2 Series IS22010051F5052
ES1024C	Magic Pak®	JMP-102-4C
ES1024STL	Magic Pak®	JMP-102-4C