

CONNECTORS



| SUPCO® Part No. | C&D® | JB® | Description |
|-----------------|--------|--------|--|
| SF2000 | CD2000 | | 1/4" MF x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2010 | CD2010 | QC-E4 | 1/4" MF x 1/4" FF Knurled Swivel 90° w/depressor tip and seal |
| SF2012 | CD2012 | | 1/2" Male ACME x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2014 | CD2014 | | 1/4" MPT x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2018 | CD2018 | | 1/8" MPT x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2019 | CD2019 | | 1/8" FPT x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2028 | CD2028 | | 1/4" MF x 1/2" Female ACME Knurled Swivel w/depressor tip and seal |
| SF2038 | CD2038 | | 3/8" MF x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2041 | CD2041 | | 1/4" FPT x 1/4" FF Knurled Swivel w/depressor tip and seal |
| SF2056 | CD2056 | | 1/4" MF x 5/16" FF Knurled Swivel 45° w/depressor tip and seal |
| SF1446 | CD1446 | D10244 | 1/4" FF Hex Swivel x 1/4" FF Hex Swivel. No depressor tips |
| SF1454 | CD1454 | | 1/4" MF x 1/4" FF Nut w/depressor tip and valve core |
| SF2594 | CD2594 | | 1/4" x 1 1/4" Long tube. Double flared with 1/4" FF Nut and depressor tip |
| SF2595 | CD2595 | | 1/4" Swaged x 1 1/4" Long tube. Double flared with 1/4" FF Nut and depressor tip |
| SF2597 | CD2597 | | 1/4" MF x 1/4" FF Nut w/depressor tip and valve core. All brass |
| SF9644 | CD9644 | | (2) 1/4" MF on u-shape, 1/4" FF and 1/4 MF on branch. (2) cores, (1) cap |
| SF5014 | CD5014 | | 1/4" MF x 1/4" FF with floating core depressor |
| SF8725 | CD8725 | | 1/4" MF x 1/4" FF hex with copper gasket. No swivel |
| SF2035 | CD2035 | QC-S4 | 1/4" MF x 1/4" FF Knurled Swivel. Gas retaining |
| SF2037 | CD2037 | | 3/8" MF x 1/4" FF Knurled Swivel. Gas retaining |
| SF2084 | CD2084 | | 1/4" MPT x 1/4" FF Knurled Swivel. Gas retaining |
| SF2090 | CD2090 | | 1/4" MF x 1/4" FF Knurled Swivel 90°. Gas retaining |
| SF2094 | CD2094 | | 1/4" FPT x 1/4" FF Knurled Swivel. Gas retaining |
| SF2098 | CD2098 | | 1/8" FPT x 1/4" FF Knurled Swivel. Gas retaining |
| SF7265 | CD7265 | | Gauge Access Line Tap with 1/4" FPT. Fits 3/8" OD tube |

TOOLS



| SUPCO® Part No. | C&D® | JB® | Description |
|-----------------|---------|---------|---|
| SF3900 | CD3900 | | Core removal tool. For 1/4" flare coupling |
| SF3910 | CD3910 | | Core remover tool with 1/4" male flare. For 1/4" flare coupling |
| SF3920 | CD3920 | A32500N | Core remover tool with ball valve. For 1/4" flare coupling |
| SF3930 | CD3930 | A32525N | Core remover tool with ball valve and 1/4" male flare. For 1/4" flare coupling |
| SF3956 | CD3956 | | Core remover tool with ball valve and 1/4" male flare. For 5/16" flare coupling |
| SF3975 | CD3975 | | Thermometer. Can be used with "SF39--" series core remover tools. |
| SF3090 | CD3090 | | Tube Piercing tool. Can be used with "SF39--" series core remover tools. |
| SF5560 | CD5560 | | Shut off stem for core remover tool without ball valve |
| SF5577 | CD5577 | | Core wrench tool for "SF39--" series core removal tools |
| SF3915 | CD3915 | | Pick to remove broken cores for "SF39--" series core removal tools |
| SF3916 | CD3916 | | Thread chaser to clean internal threads for "SF39--" series core removal tools |
| SF4311 | CD4311 | A32100 | Tube Piercing Pliers |
| SF4314 | CD4314 | A32101 | Tube Piercing Pliers Replacement Tip |
| SF3810 | CD3815 | | Valve core wrench, preset to 5 inch pounds torque. (non-adjustable) |
| SF3800 | CD3800 | A32004 | Core container/wrench. Holds (3) cores |
| SF3813 | CD3813 | | Core container/chaser/wrench. Holds (3) cores |
| SF1808 | CD1808 | A33600 | Oil Tap for semi-hermetic compressors |
| * CD2290T | CD2290T | | Locking Cap Tool |

* For use with Locking Refrigerant Caps on Page 73

