

ST06 APPLIANCE POCKET THERMOMETER



- Range: -40°F to 80°F (-40°C to 27°C)
- Mounting: Hangs Horizontally
- °F and °C Scales
- Unbreakable Lens
- For Refrigerators and Freezers

REMOTE DIAL VAPOR TENSION THERMOMETERS



- Stainless Steel Housing
- Analog Dual Scale Dial °F or °C
- 48" Capillary
- Back Connection Mounting Points
- Temperature Range -40°F to 60°F (-40° to 16°C)

Part No.	Dial Size	Flange
S6020BB	2"	Back
S6020FB	2"	Front
S6025FB	2.5"	Front
S6020HL	2"	Front
S6025HL	2.5"	Front

SSDF20 SOLAR POWERED LCD THERMOMETER



- Stainless Steel Housing
- °F or °C Selectable
- Easy to Read LCD Display
- Temperature Update Every 10 Seconds

Specifications	
Mounting	Surface front flange / Back connection
Range	-60°F to 160°F (-51°C to 71°C)
Accuracy	+/- 2°F
Dial Size	2"
LCD Display Size	3/8"
Sensor Length	60"
Update Time	10 seconds
On/Off Switch	Yes

THC120 INDOOR DIGITAL THERMO-HYGROMETER WITH CLOCK



- Table Top or Wall Mount
- Measure Temperature & Humidity Simultaneously
- Real Time Clock
- Large Triple Display
- Batteries Included 1(AAA)
- Min/Max Temperature and Humidity Memory Function
- 1 Year Warranty

Specifications	Temperature	Humidity
Range	32°F to 120°F 0°C to 50°C	10% to 90%
Resolution	0.1°F	1%
Accuracy	+/-1.8°F or 1.0°C	+/-5%

ST1236-31 SURE TEMP THERMOMETER



The Sure Temp Thermometer is the Least Expensive Device Manufactured Today to Show Exact Temperature in a Case, Reach-In, or Walk-In Cooler.

- Simulates Internal Temperature of a Refrigerated or Frozen Product
- Meets Food Service Criteria
- Includes Bracket and Screw for Easy Mounting
- Operating Temperature -40°F to 180°F

TPFDA K-TYPE THERMOCOUPLE PROBE



- Subminiature Connector with 4' Bead Tip Probe
- FDA Approved Insulation
- Temperature Range -40°F to 550°F, -40°C to 288°C