

# Weatherproof metallic boxes

## Round boxes, extensions and covers

### Applications:

- Junction for branch conduits
- Spacious, accessible wiring chamber provides a convenient location to maintain or change a system, pull conductors and make splices

### Features/Benefits:

- Copper-free\* aluminum provides increased corrosion resistance
- Precision-cast and machined surfaces permit safer wire pulling
- Clean cover edges provide good gasket sealing
- Precision NPT threads enable trouble-free field installation for rigid, IMC or EMT conduit
- Deep-slotted stainless steel cover screws for faster installation
- Clear UL® and cubic content markings speed approval by inspectors

### Standard materials:

- S Boxes: Die-cast aluminum alloy A380
- SS-B Cover: Stamped aluminum
- Gaskets: Composition

### Standard finish:

- Powder-coated finish

### Compliances:

- UL® Listed
- Federal Spec. W-C-586B
- Sample Specifications:
- Outlet boxes and covers shall be die-cast copper-free\* aluminum alloy A380 ("S"). Outlet boxes and covers shall be finished with powder-coated paint.

Outlet boxes and covers shall be Red•Dot®.  
Catalog No. \_\_\_\_\_

\* Less than .004% copper content.

\*\* S Boxes — Die-cast aluminum alloy A380.



S-47

### Boxes

Cat. No.	Color	Hub size (in.)	Description	Std. ctn.
<b>Five outlets, 4 1/8" diameter</b>				
S-47	Silver	1/2	5 Outlets, cast	36
S47CFB	Silver	1/2	Ceiling fan box and cover rated for 50 lb. Fixture or 35 lb. Fan	10
S-48	Silver	3/4	Mounting lugs, 4 closure plugs	36
S48CFB	Silver	3/4	Ceiling fan box and cover rated for 50 lb. Fixture or 35 lb. Fan	10
<b>D-PAK</b>				
DS-47	Silver	1/2	5 Outlets	8
DS-47-BR	Bronze	1/2	5 Outlets	8
DS-47-WH	White	1/2	5 Outlets	8
DS-48	Silver	3/4	5 Outlets	8
DS-48-BR	Bronze	3/4	5 Outlets	8
DS-48-WH	White	3/4	5 Outlets	8
DS-47B	Silver	1/2	With blank cover	8
DS-48B	Silver	3/4	With blank cover	8

Note: Boxes are raintight when used with appropriate Red•Dot® covers.  
All covers packed with gasket and screws.



S130E

### 4 1/2" Round extensions

Cat. No.	Color	Hub size (in.)	Description	Std. ctn.
<b>Four outlets, 4 1/8" diameter, 1 5/8" deep</b>				
S130E	Silver	1/2	4 Outlets	8
SE-48	Silver	3/4	4 Closure plugs, gasket and screws	5