

52171-OW



OW Swing Ears

4" Square Old-Work Box with Swing Ears


CAT. NO.	DESCRIPTION	STD. CTN.
52171-OW	Metallic 4"-Sq. x 2 1/8"D Old-Work Box with factory-mounted swing ears	25
OW SWING EAR	Swing Ears only (for field installation) with self-threading screws	50 (25 pair)




52151 1/2 3/4




52151 N




52151 MS N*
MS bracket for
1 1/4", 2 1/4", 3 1/4", 4"




52151 BN*
B bracket
mounted flush



52151 VN*
SV bracket
mounted flush




52151 CVN*
CV bracket
mounted flush



52151 CVNP



52171 N



52171-VN*
SV bracket
mounted flush




52141-1/2




52151 1/2




52151-3/4




521511234P




52151-3/4-W




52151B1234
B Bracket mounted flush



52151-1/2 & 3/4-EW



521511234EWGB



521511234EWGBP

4" Square Boxes

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	CLAMPS	BRKTS.	KNOCKOUTS (IN.)			STD. CONDUIT CTN.
					EA. SIDE	EA. END	BOTTOM	

With Non-Metallic Sheathed Cable Clamps

52151 N	1 1/2	21.0	C-5	—	2-1/2, 1-1/2, 3/4E	2	1-1/2	50
52151 MS N*	1 1/2	21.0	C-5	MS	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52151 BN*	1 1/2	21.0	C-5	B	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52151 VN*	1 1/2	21.0	C-5	SV	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52151 CVN*	1 1/2	21.0	C-5	CV	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52151CVNP*	1 1/2	21.0	C-5	CV	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52171 N	2 1/2	30.3	C-5	—	2-1/2, 1-1/2, 3/4E	2	1-1/2	25
52171-VN*	2 1/2	30.3	C-5	SV	2-1/2, 1-1/2, 3/4E	2	1-1/2	25

With Conduit KOs

52141-1/2	1 1/4	18.0	—	—	2-1/2, 3-1/2, 5-1/2	3-1/2	5-1/2	50
52151 1/2	1 1/2	21.0	—	—	3-1/2, 3-1/2, 5-1/2	3-1/2	5-1/2	50
52151-3/4	1 1/2	21.0	—	—	2-3/4, 2-3/4, 3-1/2, 2-3/4	3-1/2	5-1/2	50
52151 1/2 3/4	1 1/2	21.0	—	—	2-1/2, 1-3/4, 2-1/2, 1-3/4	3-1/2	5-1/2	50
521511234P	1 1/2	21.0	—	—	2-1/2, 1-3/4, 2-1/2, 1-3/4	3-1/2	5-1/2	50
52151-3/4-W	1 1/2	21.0	—	—	2-3/4, 2-3/4, 3-1/2, 2-3/4	3-1/2	5-1/2	50
52151B1234*	1 1/2	21.0	—	B	2-1/2, 1-1/2, 3/4E, 2-1/2, 1-1/2, 3/4E	3-1/2, 2-1/2, 3/4E	5-1/2	25
52151-1/2 & 3/4-EW	1 1/2	21.0	—	—	2-1/2, 1-1/2, 3/4E, 2-1/2, 1-1/2, 3/4E	3-1/2, 2-1/2, 3/4E	5-1/2	50
521511234EWGB (Ground bump)	1 1/2	21.0	—	—	2-1/2, 1-1/2, 3/4E, 2-1/2, 1-1/2, 3/4E	3-1/2, 2-1/2, 3/4E	5-1/2	50
521511234EWGBP (Ground bump with 10 1/2" ground wire)	1 1/2	21.0	—	—	2-1/2, 1-1/2, 3/4E, 2-1/2, 1-1/2, 3/4E	3-1/2, 2-1/2, 3/4E	5-1/2	50

* All Bracketed boxes come complete with eccentric knockouts.

Per UL 514-A, suitable for use without a bonding jumper in circuits above or below 250 volts. Pigtail wire is #12 AWG insulated, 10 1/2" long.