

## Mounting Bases, Cable Ties and Accessories

Designed for indoor or outdoor use and heavy-duty applications.

### Framing Channel Clamp

- Quick and easy to install on existing metal framing channel
- Installs with a push and twist
- Smooth design protects cable insulation
- Takes range of cable diameters



When fastening wire bundles, cables or hoses to framing channels, you can cut costs considerably by using the Ty-Rap® cable clamp. It's made of smooth, weather-resistant nylon and designed to protect cable insulation and hoses from wear or damage, which can occur with metal clamps. The clamp may be used for both indoor or outdoor applications. It quickly installs in the framing channel with a simple push and twist. It requires no screws, nuts or tools. The clamp fits all 1½" and 1¾" channels regardless of channel depth.




| STD. PKG. CAT. NO. | CHANNEL SIZE (IN.) | MAXIMUM TIE WIDTH ACCOM. | STD. PKG. QTY. |
|--------------------|--------------------|--------------------------|----------------|
| TC5363X            | 1½ & 1¾            | .301/7.65                | 50             |

• Made from high-impact weather-resistant black nylon  
For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

Specially designed head is range-taking.

### Ty-Rap® Mounting Base for Masonry and Brick Surfaces

- Quick, easy installation without cumbersome adhesives or epoxies
- Provides a quick, easy and dependable means of attaching cable and wires to masonry surfaces
- Installs by tapping it into a drilled hole
- It's immediately ready to accept a cable tie and wire bundle — no tedious surface preparation; no waiting for adhesives to set
- Replaces a variety of anchors, clamps, screws and adhesives
- Designed for both indoor and outdoor applications
- Only two sizes to stock — reduces inventory



| STD. PKG. CAT. NO. | HOLE SIZE IN MASONARY | MAXIMUM TIE WIDTH ACCOM. | STD. PKG. QTY. |
|--------------------|-----------------------|--------------------------|----------------|
| TC5358             | ¼                     | .190/4.83                | 100            |
| TC5359             | ⅜                     | .500/12.70               | 50             |

• Made of a special impact and ultraviolet-resistant black nylon  
For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

Weather resistant!

### Ty-Rap® Mounting Base for Lashing Tie



- For use with lashing ties up to .500" width (i.e. TY5409)
- High impact

| STD. PKG. CAT. NO. | MOUNTING METHOD | TIE WIDTH ACCOM. | MAXIMUM WIDTH IN./MM | LENGTH IN./MM | STD. PKG. QTY. |
|--------------------|-----------------|------------------|----------------------|---------------|----------------|
| TC5355             | #8 screw        | .500/12.70       | .750/19.05           | 1.750/44.45   | 25             |
| TC5356             | #10 screw       | .500/12.70       | .750/19.05           | 1.750/44.45   | 25             |
| TC5357             | ¼" screw        | .500/12.70       | .750/19.05           | 1.750/44.45   | 25             |

• Black nylon construction  
For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).