


52[®] /53[®] Series Liquidtight Fittings and Flexible Metallic Conduits

52[®] and 53[®] Series Liquidtight Straight Connectors*




CAT. NO.		CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED STEEL	NON-INSULATED STEEL		A	B	C
5229 [†]	—	1/4"	2 1/32	1 3/8	1 1/32
5330 [†]	—	3/16"	6 3/64	1 3/8	1 1/32
5331 ^{†**}	5231 [†]	3/8"	1 1/32	1 1/2	3/16
5332 [†]	5232 [†]	1/2"	1 3/8	1 9/16	9/16
5333 [†]	5233 [†]	3/4"	1 23/32	1 3/8	9/16
5334 [†]	5234 [†]	1"	1 7/8	2 1/16	3/4
5335 [†]	5235 [†]	1 1/4"	2 29/32	2 1/2	1 3/16
5336	5236	1 1/2"	2 29/32	2 11/16	1 3/16
5337	5237	2"	3 1/4	3 1/16	1/8
5338	5238	2 1/2"	3 3/4	4 1/8	1
5339	5239	3"	4 1/2	4 1/4	1
5340	5240	4"	5 1/2	4 1/2	1 1/8
5385 [†]	5285	5"	8 3/4	7	1 1/8
5386 [†]	—	6"	8 3/4	8 1/2	2



Steel/malleable iron or aluminum tapered hub threads. With safe-edge ground through 4" cone and double bevel seating ring (through 2").

52[®] and 53[®] Series Liquidtight 45° Angle Connectors*

CAT. NO.		CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED	NON-INSULATED		A	B	C
5341 ^{†**}	5241 [†]	3/8"	1 1/32	1 1/16	3/16
5342 [†]	5242 [†]	1/2"	1 3/8	1 1/8	9/16
5343 [†]	5243 [†]	3/4"	1 23/32	2 1/8	9/16
5344 [†]	5244 [†]	1"	1 7/8	2 1/4	3/4
5345 [†]	5245 [†]	1 1/4"	2 29/32	2 3/4	1 3/16
5346	5246	1 1/2"	2 29/32	3 3/8	1 3/16
5347	5247	2"	3 1/4	3 3/8	1/8
5348	5248	2 1/2"	3 3/4	4 1/4	1
5349	5249	3"	4 1/2	4 1/4	1
5350	5250	4"	5 1/2	4 3/4	1 1/8




Malleable iron, tapered hub threads. With safe-edge ground cone and double bevel sealing ring (through 2").

52[®] and 53[®] Series Liquidtight 90° Angle Connectors



CAT. NO.		HUB SIZE	CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED	NON-INSULATED			A	B	C
5351	5251	3/8"	3/8"	1 1/32	1 3/8	3/16
5352	5252	1/2"	1/2"	1 3/8	1 1/16	3/16
5353	5253	3/4"	3/4"	1 23/32	1 3/4	3/16
5354	5254	1"	1"	1 7/8	2 1/16	3/4
5355	5255	1 1/4"	1 1/4"	2 29/32	2 3/4	1 3/16
5356	5256	1 1/2"	1 1/2"	2 29/32	2 15/16	1 3/16
5357	5257	2"	2"	3 1/4	3 1/16	1/8
5358	5258	2 1/2"	2 1/2"	3 3/4	8 1/8	1
5359	5259	3"	3"	4 1/2	10 1/4	1
5360	5260	4"	4"	5 1/2	12 3/4	1 1/8



* Suitable for hazardous locations use in Class I, Div. 2; Class II, Div. 1 and 2; Class III, Div. 1 and 2, where general-purpose equipment is specifically permitted per NEC®.

** 3/8" Conduit Fitting has 1/2" hub.

† UL Listed as grounding means under NEC 350.60.

‡ Not UL Listed.

Note: UL Listed liquidtight; and CSA Certified watertight. Available with DURA-PLATE® Finish. UL File No. E-23018 CSA File No. 2884



Blue is a trademark color of Thomas & Betts.