

## Sludge Sucker®/Blaster® Kit **Sludge Sucker**® RISIOF

Nitrogen is a dry inert gas with multiple uses in the HVAC/R industry: purging and pressure testing copper

tubing, calibrating pressure controls, cleaning a condensate drain line, cleaning coils, inflating tires, unclogging a sink, operating impact tools and much more. Uniweld does not recommend that  $CO_2$  be used for purging or pressure testing an A/C&R system because it may form carbonic acid within the system, causing premature equipment failure. The Sludge Sucker<sup>®</sup> Kit options include a choice of high or low-pressure regulators for Nitrogen or CO<sub>2</sub> [with optional F36] adaptor] and various carrying stands depending on tank size. All Sludge Sucker<sup>®</sup> Kits include the handy Sludge Blaster<sup>®</sup> for quickly unclogging drain pipes.



Blow off coils with Sludge Sucker® Blowgun



Purge and pressure test an A/C&R system



UNIWELD EMPLOYS OVER 300 WORKERS

Clean out condensate drain lines with Sludge Blaster<sup>®</sup>

40004

1. Locate condensate drain line. Sludge Sucker<sup>®</sup>vinyl hose fits inside a 3/4" PVC fitting.







3. Allow Nitrogen to flow through **Sludge Sucker®** fitting and then watch the sludge get sucked out of the drain line and blown onto the ground.

Part#	Regulators	Sludge Item	Hoses	Blowgun	<b>Carrying Stand</b>
40001	R1563 [Delv. 5-175 psi]	40000			515 [20 cu. ft.]*
40002	R1563 [Delv. 5-175 psi]	Sludge	H5SMBY		516 [40/55 cu. ft.]*
40003	RHP500 [Delv. 20-500 psi]	Sucker®	5 ft. hose	BG1	515 [20 cu. ft.]*
40004	RHP500 [Delv. 20-500 psi]	40061	H2SSM		516 [40/55 cu. ft.]*
40039	RHP400 [Delv. 20-400 psi]	Sludge	2 ft. hose		515 [20 cu. ft.]*
40040	RHP400 [Delv. 20-400 psi]	Blaster®			516 [40/55 cu. ft.]*
_					*Tank not included.





Uniweld Products, Inc. Fort Lauderdale, FL 33312 U.S.A. Customer Service: 800.323.2111 info@uniweld.com • www.uniweld.com

## Sludge Sucker®Maintenance Kit **Sludge Sucker**<sup>®</sup>

A versatile, all-in-one kit that includes a Nitrogen regulator with a delivery pressure up to 400 PSI for

UNIWELD EMPLOYS OVER 300 WORK pressure testing an A/C&R system for leaks. It also includes many accessories for cleaning condensate drain lines and for blowing off coils. It even has a air chuck to fill up that flat tire. As a bonus, our Sludge Blaster® is included (see page 80 for more information). Carry stands are sold separately (see page 41).



**Blow off coils** with Sludge Sucker® Blowgun



Clean condensate drain lines with the Sludge Blaster®



Inflate tire with the Sludge Sucker® Air Chuck





Part#	Description	Part#	Description
RHP400	Nitrogen Regulator	40048	Needle Tip
40000	Sludge Sucker®	40050	<sup>1</sup> / <sub>2</sub> " Rubber Plug
40061	Sludge Blaster®	40022	<sup>3</sup> /4" Rubber Plug
H2SSM	2 Ft. Hose	BG1	Blowgun
H5SMBY	5 Ft. Hose	40045	Air Chuck

40077 Sludge Blaster® **Accessory Kit** 

Already own a Nitrogen regulator? Then this 8-piece accessory kit is for you. It attaches to your regulator and includes the most popular tools to unclog and flush drain lines.

			Description
40061	Sludge Blaster®	40050	<sup>1</sup> / <sub>2</sub> " Rubber Plug
H2SSM	2 Ft. Hose	40022	<sup>3</sup> / <sub>4</sub> " Rubber Plug
H5SMBY	5 Ft. Hose	BG1	Blowgun
40048	Needle Tip	40045	Air Chuck





Uniweld Products, Inc. Fort Lauderdale, FL 33312 U.S.A. Customer Service: 800.323.2111 info@uniweld.com • www.uniweld.com



## Now with Twice the Suction Power

**Sludge Sucker**® FORUSJOB

The Sludge Sucker<sup>®</sup> is a tool that was developed to clean out a condensate drain line without accessing the drain

pan located in the air handler. The Sludge Sucker's clear vinyl hose is attached to the 3/4" PVC condensate drain line on the outside of the building. With the use of Nitrogen or CO2, suction is created and that pulls all the sludge and algae from the drain pan and drain line; then blows it onto the ground outside.

> Use PVC fittings, if needed, to attach vinyl hose to drain line.

> > 40000

1. Locate condensate drain line. Sludge Sucker<sup>®</sup>vinyl hose fits inside a 3/4" PVC fitting.



Description

Sludge Sucker<sup>®</sup> with clear vinyl hose.

UNIWELD EMPLOYS OVER 300 WORKERS

3. Allow Nitrogen to flow through Sludge Sucker<sup>®</sup> fitting and then watch the sludge get sucked out of the drain line and blown onto the ground.

40000

Sludge Sucker®

40061 Sludge Blaster®

**1. Insert Sludge** Blaster<sup>®</sup> into the "T" connection at the air handler.



Sludge Blaster®/Drain Blaster®



**3. Replace PVC** cap on "T" connection For future service: **DO NOT GLUE** PERMANENTLY.

2. Allow Nitrogen (at max. 140 PSIG) to flow through, blasting the sludge free.

> Unclog A/C condensate drain pipes FAST with Sludge Blaster®. It expands inside the pipe and with pressure exerted on the clog, blasts the sludge free. Attaches to standard 1/4" service hose. Pipe capacity: 3/4" to 1" I.D.

Unclog drain pipes FAST with Drain Blaster®. It expands inside the pipe and exerts water pressure on the clog...blasting it free. Attaches to standard 3/4" garden hose.

40064

Part#	Description	Pipe Capacity
40061	Sludge Blaster®	<sup>3</sup> / <sub>4</sub> " to 1" I.D.
40062	Drain Blaster™	1" to 2" I.D.
40063	Drain Blaster™	$1\frac{1}{2}$ " to 3" l.D.
40064	Drain Blaster™	3" to 6" I.D.

Uniweld Products, Inc. Fort Lauderdale, FL 33312 U.S.A. Customer Service: 800.323.2111 info@uniweld.com • www.uniweld.com



40062

40063

