

## PEX-a Pipe Support

Submittal Information

Revision D: Dec. 23, 2014

### Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

### Technical Data

Material: Commercial-grade (Type B) galvanized steel



### Product Information and Application Use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.

✓ Description	Part Number	Height	Width	Length	Gauge	Weight
½" PEX-a Pipe Support, 9-ft. length	F7040500	0.42"	0.75"	108"	23	1.10 lbs.
¾" PEX-a Pipe Support, 9-ft. length	F7040750	0.56"	1.00"	108"	23	1.50 lbs.
1" PEX-a Pipe Support, 9-ft. length	F7041000	0.64"	1.13"	108"	23	1.91 lbs.
1¼" PEX-a Pipe Support, 9-ft. length	F7041250	0.79"	1.38"	108"	23	2.10 lbs.
1½" PEX-a Pipe Support, 9-ft. length	F7041500	0.93"	1.63"	108"	23	2.50 lbs.
2" PEX-a Pipe Support, 9-ft. length	F7042000	1.14"	2.00"	108"	23	3.60 lbs.
2½" PEX-a Pipe Support, 9-ft. length	F7042500	1.25"	2.52"	108"	23	4.60 lbs.
3" PEX-a Pipe Support, 9-ft. length	F7043000	1.90"	3.12"	108"	23	6.20 lbs.
3½" PEX-a Pipe Support, 9-ft. length	F7043500	2.16"	3.60"	108"	23	6.40 lbs.

### Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

### Accessories

Q7410510: PEX-a Pipe Support Strapping (½", ¾", 1" PEX)

Q7411220: PEX-a Pipe Support Strapping (1¼", 1½", 2" PEX)

Q7412540: PEX-a Pipe Support Strapping (2½", 3", 3½", 4" PEX)

### Standards

ASTM E84 (up to 3")

### Codes

IMC, UMC, NBCC

### Listings

QAI P321 (up to 3")

### Related Applications

PEX-a Plumbing Systems  
Radiant Heating and Cooling Systems  
AquaSAFE™ Fire Safety Systems

### Contact Information

Uponor, Inc.  
5925 148th Street West  
Apple Valley, MN 55124 USA  
Phone: 800.321.4739  
Fax: 952.891.2008  
www.uponorpro.com

Uponor Ltd.  
2000 Argentia Rd., Plaza 1, Ste. 200  
Mississauga, ON L5N 1W1 CANADA  
Phone: 888.994.7726  
Fax: 800.638.9517  
www.uponorpro.com