

## PEX Crimp

With the reliability and quality required for potable water systems, Viega PEX Crimp fittings are part of Viega's complete plumbing solution. Matched with the revolutionary Viega ManaBloc water distribution system and the PEX tubing that meets the highest standards in the industry, Viega PEX Crimp fittings are a time-tested method of joining PEX.

### FEATURES AND BENEFITS

- EcoBrass® fittings provide better corrosion resistance than other brass fittings
- High-performance PolyAlloy fittings are made in the USA
- Peace of mind from durable materials and quality manufacturing
- Available in sizes  $\frac{3}{8}$ " to 1"
- 25-year limited warranty

### CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristics
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ICC: International Plumbing Code
- IAPMO: Uniform Plumbing Code
- NSF/ANSI 61: Drinking Water System Components - Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

### ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).


**Viega PEX 90° compression elbow  
Zero Lead**

- For dishwasher, connecting  $\frac{3}{8}$ " compression to  $\frac{3}{4}$ " hose supply connection
  - Equipped with ferrule Part No 53015
  - Copper
  - Hose connection
- Model V5053**

CTS	Hose	Wt [lb]	Quantity	Part No	DG
$\frac{3}{8}$	$\frac{3}{4}$	0.155	1	<b>46743</b>	2


**Viega PEX Crimp 90° elbow**

- Copper
  - Crimp connection, female copper tube size
- Model V5021**

Crimp	C	Wt [lb]	Quantity	Part No	DG
$\frac{1}{2}$	$\frac{1}{2}$	0.048	50	<b>44325</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	0.111	25	<b>44345</b>	2


**Viega PEX Crimp 90° elbow**

- Copper
  - Crimp connection, street
- Model V5020**

Crimp	FTG	Wt [lb]	Quantity	Part No	DG
$\frac{1}{2}$	$\frac{1}{2}$	0.045	50	<b>44320</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	0.100	25	<b>44340</b>	2

**Tees**

**Viega PEX Crimp tee  
Zero Lead**

- Brass
  - Crimp connection
- Model V5018ZL**

Crimp1	Crimp2	Crimp3	Wt [lb]	Quantity	Part No	DG
$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	0.062	50	<b>46500</b>	2
$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	0.057	50	<b>46520</b>	2
$\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{4}$	0.077	25	<b>46524</b>	2
$\frac{3}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	0.096	25	<b>46433</b>	2
$\frac{3}{4}$	$\frac{1}{2}$	$\frac{3}{4}$	0.101	25	<b>46435</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	$\frac{1}{2}$	0.102	25	<b>46443</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	$\frac{3}{4}$	0.100	25	<b>46540</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	1	0.196	10	<b>46445</b>	2
1	$\frac{3}{4}$	$\frac{3}{4}$	0.196	10	<b>46544</b>	2
1	$\frac{3}{4}$	1	0.203	10	<b>46545</b>	2
1	1	$\frac{1}{2}$	0.182	10	<b>46553</b>	2
1	1	$\frac{3}{4}$	0.161	10	<b>46554</b>	2
1	1	1	0.213	10	<b>46560</b>	2


**Viega PEX Crimp tee**

- PolyAlloy
  - Crimp connection
- Model V5218**

Crimp1	Crimp2	Crimp3	Wt [lb]	Quantity	Part No	DG
$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	0.005	50	<b>43500</b>	3
$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	0.014	50	<b>43520</b>	3
$\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{4}$	0.019	25	<b>43334</b>	3
$\frac{3}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	0.021	25	<b>43433</b>	3
$\frac{3}{4}$	$\frac{1}{2}$	$\frac{3}{4}$	0.026	25	<b>43434</b>	3
$\frac{3}{4}$	$\frac{3}{4}$	$\frac{1}{2}$	0.023	25	<b>43443</b>	3
$\frac{3}{4}$	$\frac{3}{4}$	$\frac{3}{4}$	0.029	25	<b>43540</b>	3
$\frac{3}{4}$	$\frac{3}{4}$	1	0.038	10	<b>43445</b>	3
1	$\frac{3}{4}$	$\frac{3}{4}$	0.047	10	<b>43544</b>	3
1	$\frac{3}{4}$	1	0.054	10	<b>43545</b>	3
1	1	$\frac{1}{2}$	0.043	10	<b>43553</b>	3
1	1	$\frac{3}{4}$	0.046	10	<b>43554</b>	3
1	1	1	0.059	10	<b>43560</b>	3

**Adapters**

**Viega PEX Crimp adapter  
Zero Lead**

- Brass
  - Crimp connection, male pipe thread
- Model V5011ZL**

Crimp	MPT	Wt [lb]	Quantity	Part No	DG
$\frac{3}{8}$	$\frac{1}{2}$	0.102	50	<b>46302</b>	2
$\frac{1}{2}$	$\frac{1}{2}$	0.101	50	<b>46321</b>	2
$\frac{1}{2}$	$\frac{3}{4}$	0.141	25	<b>46324</b>	2
$\frac{3}{4}$	$\frac{1}{2}$	0.096	25	<b>46342</b>	2
$\frac{3}{4}$	$\frac{3}{4}$	0.147	25	<b>46340</b>	2
$\frac{3}{4}$	1	0.216	10	<b>46446</b>	2
1	$\frac{3}{4}$	0.155	10	<b>46361</b>	2
1	1	0.236	10	<b>46366</b>	2