

## **PEX Press**

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water systems. With PEX tubing that meets the highest standards in the market, the revolutionary Viega ManaBloc, and Viega PEX Press manifolds in highperformance polymer, Viega PEX Solutions work together to save time, labor and cost. The first press system for the PEX market, Viega PEX Press fittings improve consistency and reduce installation errors with factory-attached sleeves. Available in high-performance polymer and Viega Zero Lead bronze. Viega PEX Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions, and system-matched tools and jaws make installation easy and consistent. Viega PEX Solutions also includes the versatile Viega FostaPEX multilayered tubing for plumbing and radiant heating applications, designed to be both rigid and highly flexible while holding its shape for plumbing and radiant heating applications.

### **FEATURES AND BENEFITS**

- · The original press fitting for PEX tubing
- Factory-assembled press fittings reduce installation errors on the iob
- Available in sizes from 3/8" to 2"
- The only PEX fittings with the Viega Smart Connect feature
- 25-year limited warranty

#### **CODES AND STANDARDS**

- ASTM E84: Specification for Surface Burning Characteristic
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- NSF/ANSI 61: Drinking Water System Components Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content</li>
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service
- D UL 263 Fire Tests of Building Construction and Materials

#### **ZERO LEAD**

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

#### NOTE

A Green Dot on a Viega PEX Press fitting indicates the Smart Connect feature.





# Viega PEX Press tee **Smart Connect feature**

- Polymer
- tion

•	Pres	ss (	coni	necti	
۸.	Made		1561	0	

P1	P2	P3	Wt [lb]	Quantity	Part No	DG
3/8	3/8	3/8	0.035	25	49200	6
1/2	3/8	3/8	0.036	25	49322	6
1/2	1/2	3/8	0.039	25	49332	6
1/2	1/2	1/2	0.042	25	49520	6
1/2	1/2	3/4	0.052	25	49334	6
3/4	1/2	1/2	0.052	25	49433	6
3/4	1/2	3/4	0.061	25	49434	6
3/4	3/4	1/2	0.059	25	49443	6
3/4	3/4	3/4	0.068	25	49540	6
1	1/2	1/2	0.068	10	49533	6
1	1/2	1	0.097	10	49535	6
1	3/4	1/2	0.074	10	49543	6
1	3/4	3/4	0.084	10	49544	6
1	3/4	1	0.104	10	49545	6
1	1	1/2	0.088	10	49553	6
1	1	3/4	0.102	10	49554	6
1	1	1	0.115	10	49560	6
11/4	1	3/4	0.150	5	49754	6
11/4	1	1	0.166	5	49755	6
11/4	11/4	3/4	0.182	5	49774	6
11/4	11/4	1	0.206	5	49775	6
11/4	11/4	11/4	0.250	5	49570	6
11/2	1	3/4	0.170	5	49854	6
11/2	1	1	0.195	5	49855	6
11/2	11/4	3/4	0.205	5	49874	6
11/2	11/4	1	0.225	5	49875	6
11/2	11/4	11/4	0.275	5	49877	6
11/2	11/2	1/2	0.022	1	49883	6
11/2	11/2	3/4	0.233	5	49884	6
11/2	11/2	1	0.245	5	49885	6
1½	1½	11/4	0.290	5	49887	6
11/2	11/2	1½	0.326	5	49580	6
2	11/2	3/4	0.022	1	49984	6
2	11/2	1	0.315	1	49985	6
2	11/2	11/4	0.365	1	49987	6
2	1½	1½	0.390	1	49988	6
2	2	1/2		1	49993	6
2	2	3/4	0.355	1	49994	6
2	2	1	0.373	1	49995	6
2	2	11/4	0.405	1	49997	6
2	2	1½	0.435	1	49998	6
2	2	2	0.500	1	49590	6



## **PEX Press tee arrestor** Zero Lead

- Brass

Components

Water hammer arrestor

Model 2894ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.235	10	97114	6

# **Adapters**



# Viega PEX Press adapter Zero Lead

- Bronze
- Press connection, male pipe thread Model 2811ZL

Р	MPI	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.101	10	90506	6
1/2	1/2	0.100	10	90521	6
1/2	3/4	0.152	10	90526	6
3/4	1/2	0.112	10	90542	6
3/4	3/4	0.158	10	90541	6
3/4	1	0.283	10	90546	6
3/4	11/4	0.507	2	90562	6
1	3/4	0.184	10	90556	6
1	1	0.283	10	90561	6
1	11/4	0.514	2	90566	6
11/4	11/4	0.561	2	90571	6
1½	11/2	0.678	2	90581	6
2	2	1.104	5	90591	6