

LITE INVISILED®



Power: 2W / ft
 Lumens: Up to 150 lm / ft
 CRI: 85
 Rated Life: 50,000 hours

- Specially rated for installation in the storage area of a clothes closet
- UV stabilized protective coating protects LEDs and circuitry for long term use in damp locations
- May field cut every 2 inches at the end of a run
- Includes an end cap
- Max run length of 40 feet per power supply



TAPE SELECTIONS

System	Color Temp	Length	Qty	Finish
LED-T24	27L 2700K 30L 3000K	2IN 2 inches	1	WT White
		2IN10 2 inches	10	
		1 1 foot	1	
		5 5 feet	1	
		1-40 1 foot	40	

Example: **LED-T2427L-5-WT**




"L" CONNECTOR




System	Color Temp	Finish
LED-T24	27L 2700K	3L-WT White
	30L 3000K	

Example: **LED-T2427L-3L-WT**

Each "L" connector consumes 0.7 Watts



COMPATIBLE CLASS 2 POWER SUPPLY (REQUIRED)

Type	Model	Input	Output	Dimming
Remote	 EN-2460-RB2-T EN-24100-RB2-T	120VAC	24VAC / 60W	ELV
		120VAC	24VAC / 96W	ELV
Remote	 EN-24100-277-RB2-T	120 - 277VAC	24VDC / 96W	0-10V
Plug-in	 EN-2460-P-AR-T EN-24100-P-AR-T	120VAC	24VAC / 60W	Includes a 6 foot lead wire
		120VAC	24VAC / 96W	