

PE X PE FITTINGS



CON-STAB ID SEAL® 3-Way Tees

PE SIZE	WALL	PART NUMBER (3408/4710)	PART NUMBER (2406)
1/2" CTS (5/8" OD)	.090	3259-50-1004-00†‡	3369-50-1004-00‡
3/4" CTS (7/8" OD)	.090	3259-50-1006-00‡	3369-50-1006-00
1" CTS (1 1/8" OD)	.099/.101	3259-50-1008-00†‡	3369-50-1008-00‡
	.090	3259-50-1008-AA‡	3369-50-1008-AA‡
	.121	3259-50-1008-BB	Not Available
1 1/4" CTS (1 3/8" OD)	.121	3259-50-1039-00	3369-50-1039-00
	.090	3259-50-1039-AA	3369-50-1039-AA
1/2" IPS	SDR-9.33 (.090)	3259-50-1012-00‡	3369-50-1012-00
3/4" IPS	SDR-11 (.095)	3259-50-1013-00†‡	3369-50-1013-00‡
1" IPS	SDR-11 (.119)	3259-50-1014-00†‡	3369-50-1014-00‡
1 1/4" IPS	SDR-10 (.166)	Not Available	3369-50-1015-00
	SDR-11 (.151)	3259-50-1015-AA	Not Available
1 1/2" IPS	SDR-11 (.173)	3259-50-1016-00‡	3369-50-1016-00†‡
2" IPS	SDR-11 (.216)	3259-50-1017-00†‡	3369-50-1017-00



- For sizes not listed, contact Continental Industries.
- Con-Stab ID Seal® fittings rated at 125 psig.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- † = CSA Approved / ‡ = IAPMO/UPC Listed

CON-STAB ID SEAL® 90° Elbows

PE SIZE	WALL	PART NUMBER (3408/4710)	PART NUMBER (2406)
1/2" CTS (5/8" OD)	.090	3259-51-1004-00†	3369-51-1004-00
3/4" CTS (7/8" OD)	.077	9959-51-0016-00	Not Available
	.090	3259-51-1006-00‡	3369-51-1006-00
1" CTS (1 1/8" OD)	.099/.101	3259-51-1008-00	3369-51-1008-00
	.090	3259-51-1008-AA	3369-51-1008-AA
	.121	3259-51-1008-BB	Not Available
1 1/4" CTS (1 3/8" OD)	.121	3259-51-1039-00	3369-51-1039-00
	.090	3259-51-1039-AA	3369-51-1039-AA
1/2" IPS	SDR-9.33 (.090)	3259-51-1012-00‡	3369-51-1012-00
3/4" IPS	SDR-11 (.095)	3259-51-1013-00†‡	3369-51-1013-00
1" IPS	SDR-11 (.119)	3259-51-1014-00†‡	3369-51-1014-00
1 1/4" IPS	SDR-10 (.166)	Not Available	3369-51-1015-00
	SDR-11 (.151)	3259-51-1015-AA	Not Available
1 1/2" IPS	SDR-11 (.173)	3259-51-1016-00‡	3369-51-1016-00†‡
2" IPS	SDR-11 (.216)	3259-51-1017-00†‡	3369-51-1017-00



- For sizes not listed, contact Continental Industries.
- Con-Stab ID Seal® fittings rated at 125 psig.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- † = CSA Approved / ‡ = IAPMO/UPC Listed

