


Professional Grade Duct Tape



Backing

Adhesive



- Backing:** PE Coated Cloth
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Silver, Black, White, Blue, Brown, Green
OD, Red, Tan, Yellow
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 55m, 72mm x 55m

Applications

- Hanging and patching polyethylene sheeting
- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- Seaming and securing underlayment materials
- Sealing polyethylene waste disposal bags
- Color coding
- General repair
- Bundling, patching, and mending

Features

- PE-Coated Cloth Backing
- Natural Rubber Adhesive
- Low VOC Content

Benefits

- Excellent balance of tensile strength and tearability
- Available in a wide range of colors
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11.0 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC-101
Tensile Strength	26 lb/in	45.53 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Elongation	21%		ASTM D-1000
Smoke Developed	5		UL 723
Flame Spread	5		UL 723
VOC Content	<1 g/L		

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS COMPANY, 25 Forge Parkway Franklin, MA 02038 by qualified technical personnel. To BERRY PLASTICS knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.