

Plug-On Combination Type Arc Fault Circuit Breakers, Type BR—10 kAIC, 120 Vac and 120/240 Vac

BRCAF115



Type BR, 1-Inch (25.4 mm) wide FIRE-GUARD Combination Type AFCI Circuit Breakers

Poles	Ampere Rating	Configuration	Catalog Number
Single-pole 10 kAIC	15	AFCI	BRCAF115 ^①
		Diagnostic AFCI	BRACAF115
	20	AFCI	BRCAF120 ^①
		Diagnostic AFCI	BRACAF120
Single-pole 22 kAIC	15	AFCI	BRHCAF115 ^①
	20	AFCI	BRHCAF120 ^①
Two-pole 10 kAIC	15	AFCI	BRL215CAF
	20	AFCI	BRL220CAF

Plug-On Ground Fault Circuit Breakers, Type GFCB and GFEP—10/22 kAIC, 120 Vac and 120/240 Vac


Type GFCB Single-Pole



Type GFCB Two-Pole



Type GFCB Ground Fault Circuit Breakers—5 Milliampere—1-Inch (25.4 mm) per Pole 120 Vac or 120/240 Vac, 10 kAIC

Ampere Rating	Wire Size Range Cu/Al 60°C or 75°C	 Single-Pole 120 Vac Requires One 1-Inch (25.4 mm) Space 1 per Shelf Carton Catalog Number ^②		 Two-Pole 120/240 Vac Common Trip Requires Two 1-Inch (25.4 mm) Spaces 1 per Shelf Carton Catalog Number	
15	#14–4	GFCB115		GFCB215	
20	#14–4	GFCB120		GFCB220	
25	#14–4	GFCB125		GFCB225	
30	#14–4	GFCB130		GFCB230	
40	#14–4	GFCB140		GFCB240	
50	#14–4	—		GFCB250 ^③	
60	#14–6	—		GFCB260	

Notes

- ^① Clamshell packaging available with CS modification code on the end of catalog number.
- ^② Available with bell alarm or auxiliary switch. See circuit breaker accessories on **Page V1-T1-81**.
- ^③ For use with copper wire only.