



SPLIT RING HANGER 455

Malleable Iron Split Ring Stand-Off Hanger

- Size Range: 3/8" through 4"
- Surface Finish: Electro-zinc plated
- Recommended for the suspension of stationary non-insulated pipe lines
- Allows for piping runs close to ceiling or walls
- Conforms with Federal Specification WW-H-171 (Type 25), Manufacturers Standardization Society (MSS) SP-58 and SP-69 (Type 12)
- Bolt and rivet are carbon steel



Part Number	Nominal Pipe Size	RS	A	B	Max. Rec. Load (lbs)
Plain Finish					
4550037PL	3/8"	3/8"	1-5/16"	3/8"	180
4550050PL	1/2"	3/8"	1-1/2"	3/8"	180
4550075PL	3/4"	3/8"	1-3/4"	7/16"	180
4550100PL	1"	3/8"	2"	7/16"	180
4550125PL	1-1/4"	3/8"	2-3/8"	1/2"	180
4550150PL	1-1/2"	3/8"	2-5/8"	1/2"	180
4550200PL	2"	3/8"	3-1/8"	1/2"	180
4550250PL	2-1/2"	1/2"	3-3/4"	5/8"	300
4550300PL	3"	1/2"	4-3/8"	5/8"	300
4550400PL	4"	1/2"	5-3/8"	11/16"	300
Electro-zinc Plated Finish					
4550037EG	3/8"	3/8"	1-5/16"	3/8"	180
4550050EG	1/2"	3/8"	1-1/2"	3/8"	180
4550075EG	3/4"	3/8"	1-3/4"	7/16"	180
4550100EG	1"	3/8"	2"	7/16"	180
4550125EG	1-1/4"	3/8"	2-3/8"	1/2"	180
4550150EG	1-1/2"	3/8"	2-5/8"	1/2"	180
4550200EG	2"	3/8"	3-1/8"	1/2"	180
4550250EG	2-1/2"	1/2"	3-3/4"	5/8"	300
4550300EG	3"	1/2"	4-3/8"	5/8"	300
4550400EG	4"	1/2"	5-3/8"	11/16"	300

