







PushGard™ Push-in Wire Connectors

Easy and fast to use, just strip and push conductors into PushGard™ connectors to make reliable, secure connections.

- Simplified insertion and compact size helps in tight locations.
- Clear polycarbonate housings have color-coded side panels for connection verification and identification.
- With corrosion-resistant stainless steel springs, PushGard™ connectors restrict wire pullout, yet corrections are possible with a simple left-right twist and pull.
- Continuity test point for easy voltage checks.
- Available in 2-,3-,4 and 8-port configurations.
- Rated at 600 V Max. in building wire and at 1000 V Max. in lighting fixtures/luminaries.
- Copper-to-copper connections only.



| | Color | Ports | Part # | Pkg Qty | Wire Range |
|-----|-------|-------|--------|---------|--|
| PC2 | | 2 | 10-PC2 | 100/box | #22 - #12 AWG Solid (connections rated at 600 V Max.) |
| | | | 19-PC2 | 10/clam | |
| PC3 | | 3 | 10-PC3 | 100/box | #22 - #12 AWG Solid (connections rated at 600 V Max.) |
| | | | 19-PC3 | 10/clam | |
| PC4 | | 4 | 10-PC4 | 100/box | #22 - #12 AWG Solid (connections rated at 600 V Max.) |
| | | | 19-PC4 | 10/clam | |
| PC8 | | 8 | 10-PC8 | 50/box | #22 - #12 AWG Solid (connections rated at 600 V Max.) |
| | | | 19-PC8 | 10/clam | |



Nylon Pigtail Connectors

Closed-end crimp connector designed for use with solid or stranded wire.

- Vibration resistant.
- Tin-plated seamless copper.
- Corrosion and chemical resistant.



| Part # | Pkg Qty | Wire Range | Min | Max |
|--------|---------|---------------|-------|---------------|
| 20-089 | 10/clam | #22 - #14 AWG | 2 #22 | 1 #14 w/1 #18 |
| 15-090 | 15/clam | #22 - #10 AWG | 3 #18 | 1 #10 w/1 #20 |
| 20-090 | 10/clam | #22 - #10 AWG | 3 #18 | 1 #10 w/1 #20 |

