

520PA





UPC Code: 07847784206 Country Of Origin: Mexico

*Eligible for ARRA funded projects > \$7,443,000

NEMA: 5-20P





520PA

Brand Features

Leviton offers a large selection of 15, 20, 30 and 50 Amp Commercial Grade Straight Blade Plugs and Connectors, available in a wide variety of features. These rugged performers are moisture, chemical and abuse-resistant, And they're ideal for indoor and outdoor use. Our EPTR rubber-backed plugs and connectors stand up to rough use, protecting against dirt and moisture. The deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.

Item Description

20 Amp, 125 Volt, NEMA 5-20P, 2P, 3W, Plug, Straight Blade, Commercial Grade, Armored, Grounding - Steel

Technical Information

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Voltage: 125 Volt

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 20 Amp

Wire: 3 Pole: 2

Environmental Specifications

Operating Temperature: -40C to 60C Flammability: Rated V-2 per UL94

Material Specifications

Body Material: PVC / Steel

Color: Yellow

Blades/Contacts: Brass

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 18-12 AWG Cord Range: .245 - .655

Product Features Color: Yellow

Cord Range: .245 - .655

NEMA: 5-20P

Standards and Certifications Warranty: 10-Year Limited

CSA C22.2 No. 42: File LR-406

ANSI: C-73

UL498: File E13393

NOM: 057 NEMA: WD-6

Dimensional Diagram 1.38 (35.1 mm) 1.89 (48.1 mm) 1 1.55 (39.2 mm) North American Green Dot • Represents the Ground Sleeve of Female Devices Connectors & Receptacles) 12 1 10 3Ø/250 VAC 3-pole, 4-wire 3ØY120/208 VAC 4-pole, 5-wire 3Ø380 VAC, 50Hz 3Ø440 VAC, 60Hz 3-pole, 4-wire 110 VAC 2-pole, 3-wire 125 VAC 2-pole, 3-wire 480 VAC 2-pole, 3-wire 3Ø480 VAC 3-pole, 4-wire 3ØY347/600 VAC 4-pole, 5-wire 3Ø/600 VAC 3-pole, 4-wire 3ØY277/480 VAC 4-pole, 5-wire 380-415 VAC 3-pole, 4-wire 200/346-240/415 VAC 4-pole, 5-wire Rated Voltage 110V-130V 125V-250V 200V-250V 277V, 380V, 440V 500V and above 125V W SYS G GR **EQUIP ●** G GR 5-20P

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/



