

# ACCUMULATORS

## SUCTION LINE

**Features:**

- \* Solid copper connections.
- \* U-Tube design for maximum flow of refrigerant and minimum oil entrapment.
- \* Inlet Flow Director guides refrigerant toward wall for smooth tangential flow and gradual expansion.
- \* U-Tube Entrance is positioned behind the Inlet Flow Director to prevent unwanted liquid refrigerant from entering and damaging the compressor.
- \* Metering Orifice matched to system capacity assures optimum liquid refrigerant and oil flow back to compressor.
- \* Protective Screen and Orifice Assembly on U-Tube protects against foreign particles and contaminants affecting metering function.
- \* Fittings and U-Tube are matched to accumulator holding capacity and total system charge for minimum pressure drop and maximum refrigerant flow.
- \* U.L. listed for 1775 psig bursting pressure.



Model Number	Solder Fitting Size	Dimensions (inches)		Capacity (oz.)	PARTNERS CHOICE Part Number
		Length	O.D.		
PA4065-9-6C	3/4"	9.62"	4"	58	668793
PA4065-11-6C	3/4"	11.33"	4"	52	668906
PA45083-9-6C	3/4"	9.62"	4"	89	668853
PA5083-9-7C	7/8"	9.62"	5"	86	668794
PA5083-12-7C	7/8"	12.88"	5"	125	668854
PA6125-15-9C	1 1/8"	12.88"	6"	125	669294

No Matter What Hand You're Dealt.  
It's a Winner With A  
**Wildcard!**

What's a WildCard?

- WildCard motors are universal, multi-horse power condenser and blower motors.
- WildCard gives you and your Dealer the ability to stock fewer part numbers because the WildCard replaces multiple motors.
- WildCard will work in Rheem and Ruud applications (separate mounting holes).

*Partners Choice has shuffled up a winner.*

By Partners Choice