

4700 W. 160th St. Cleveland, Ohio 44135 Ph: (800) 321-9532 Fax: (800) 321-9535 www.oatey.com


# **PVC Top Grates For Floor Sinks**



#### **SUBMITTAL SPECIFICATION**

**Engineering Specification:** Oatey Top Grates for use with Oatey Floor Sinks provide easy access to sump for debris removal & cleaning. Removable light duty grate with large open area is designed for handling large amounts of water.


Job Reference



## Full Top Grate - 42753

Total Open Area - 29.50 in.² Load - Light Duty


.75



## Three-Quarter Top Grate - 42752

Total Open Area - 37.20 in.<sup>2</sup> Load - Light Duty Condensate Area - 15.20 in.<sup>2</sup>

.75



#### Half Top Grate - 42751

Total Open Area - 46.80 in.<sup>2</sup> Load - Light Duty Condensate Area - 32.10 in.<sup>2</sup>

.75

(All dimensions in inches)

Grate Properties					
	Description	Finish	Total Open Area	Load*	Part Number
	Full Top Grate	White PVC	29.50 in. <sup>2</sup>	Light	42753
	Three-Quarter Top Grate	White PVC	37.20 in. <sup>2</sup>	Light	42752
	Half Top Grate	White PVC	46.80 in. <sup>2</sup>	Light	42751

<sup>\*</sup> Load is defined by ASME A112.21.1M. Light Duty – Safe live load under 2000 lbs.

Data is subject to manufacturing tolerances.

All Dimensions and Materials meet ASTM D2665