

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 68

Johni Ring®+ Wax Gasket

Date Prepared: 1/28/1987 Last Reviewed: 6/22/2010

Meets OSHA 29 CFR 1910.1200



**MATERIAL
SAFETY
INFORMATION
SERVICE**

Hercules Chemical Company Inc.
111 South Street
Passaic NJ 07055
Phone (800) 221-9330
Fax (800) 333-3456

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;
Common Name(s), CAS Numbers)

OSHA PEL

ACGIH TLV

Other Limits

Upper Bound
Limit if SARA
Reportable

This product is defined as an "article" and is not classified as hazardous in accordance with OSHA 1910.1200

HMIS Hazard Rating: Health: 0 Flammability: 1 Reactivity: 0 Personal Protection: A

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):	Specific Gravity (H ₂ O = 1):	Vapor Density (Air = 1):	Vapor Pressure (mm Hg):
N/A	.82 to .86	N/A	0.01
Melting Point (°F):	Evaporation Rate: (Butyl Acetate = 1)	Solubility in Water:	
140° to 170° F	N/A	Insoluble	VOC Level: 0 g/l
Appearance And Color:	Soft amber to brown color	Odor:	No odor

Section 4 - Fire And Explosion Hazard Data

Flash Point:	Flammable Limits:	LEL:	UEL:
450° F to 550° F	N/D	N/A	N/A

Extinguishing Media: Use water fog, foam, dry chemical, or CO₂. Do not use a direct stream of water.

Special Firefighting Procedures:

When handling wax fires do not enter confined space without proper protective equipment. Cool fire exposed containers with water.

Unusual Fire And Explosion Hazards:

When heated above its flash point can release flammable vapors which can burn or be explosive in confined spaces if exposed to sources of ignition.

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable **Conditions To Avoid:** High heat temperatures over 160° F

**Incompatibility
(Materials To Avoid):** Avoid strong oxidants

Hazardous Decomposition: CO and CO₂ and unidentified organic compounds may be formed during combustion.

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry: **Inhalation** N/A **Skin** YES/Secondary **Ingestion** YES/Secondary

Health Hazards:

None known

Carcinogenicity: **NTP** NO **IARC** NO **OSHA Regulated** NO

Signs And Symptoms of Exposure:

None

Medical Conditions Generally Aggravated By Exposure:

None

Emergency And First Aid Procedures:

SKIN: Wash with soap and water. **EYES:** As with all foreign material, flush eyes with water. If irritation occurs, consult a physician. **INGESTION:** No significant adverse health effects are expected. Consult a physician if large quantities are ingested.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:**Steps To Be Taken In Case Material Is Released Or Spilled:**

Sweep up spilled material in containers for disposal.

Waste Disposal Method:

Non-hazardous landfill.

Precautions To Be Taken In Handling And Storing:

Do not store over 110° F to prevent the rings from melting or deforming in shape.

Other Precautions:

None

Section 8 - Control Measures:**Respiratory Protection:**

Not required

Ventilation: Local Exhaust Adequate
Mechanical N/A

Special N/A

Other: N/A

Gloves: Not required

Eye Protection: Safety glasses

Other Protective
Clothing: None

Work/Hygienic Practices None



For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.