

Ice Machine Cleaners

Place Nos. **2RZX2** and **2RZX3** in the water sump of the ice machine to prevent slime. Nos. **1VNK1** and **4E838** are USDA accepted. Nos. **1VNK2** and **3VJ61** are metal-safe formulas. No. **3TA74** is a powder with corrosion inhibitor.



No. **3TA74**



No. **1VNK1**

Size	Brand	Mfr. Model	Item No.	\$ Each
8 Oz.	Nu-Calgon	4209-05	2RZX2	73.20
6 Oz.	Nu-Calgon	4209-06	2RZX3	85.10
16 Fl. Oz.	Virginia KMP	H418-G	1VNK1	12.96
16 Fl. Oz.	Virginia KMP	H420-G	1VNK2	8.61
1 Gal.	Virginia KMP	H421	3VJ61	75.70
1 Gal.	Virginia KMP	H419	4E838	86.60
4.4 Fl. Oz.	Highside Chemical	50004	3TA74	9.97

Drain Clearing Gun



CO₂-powered gun clears clogged condensate drains. Fits 3/8 to 3/4" drain openings. Max. working pressure: 800 psi.



No. **1GDL7**



No. **1GDL8**

Description	Mfr. Model	Item No.	\$ Each
Drain Clearing Gun	GG-1	1GDL7	69.55
Replacement CO ₂ Cartridge, Pkg. of 12	GGC-12	1GDL8	29.40

Refrigerator Coil Brush

Large-diameter brush has wooden handle and soft, white bristles that gently remove lint from refrigerator coils without damaging fan blades.

Fill Type	Brush Dim. (In.) L Dia.		Handle Dim. (In.) L Dia.		Overall Length (In.)	Item No.	\$ Each
Polyester	12	3/4 to 1½	15	5/8	28	2KVE3	7.45



Rust-Breaking Aerosol

Rapid freezing action shrinks seized or rusted components to allow lubricant to act.

Size/Net Weight	Temp. Range (°F)	Brand	Mfr. Model	Item No.	\$ Each
9 Oz.	-40 to 130	Virginia KMP	NB9	2RZW1	18.23



Refrigeration Lubricants and Oils

EMKARATE™ RL POLYOL ESTER LUBRICANTS

OEM-approved for use with HFCs, HCFCs, and traditional CFC refrigerants. No wax content, and no floc point. Quality assurance registered to BS5750. Nos. **2NTK1** to **2NTK3** are approved for Copeland compressors.

Note: EMKARATE is a trademark of Unequema. For grades not listed, contact your local branch.

ISO Viscosity	Viscosity SUS @ 100°F	Container Size	Mfr. Model	Item No.	\$ Each
EMKARATE™ RL Polyol Ester Lubricants					
32	150	1 Qt.	LE32HQ	1K467	41.80
32	150	1 Gal.	LE32H1	2NTK4	107.05
32	150	1 Qt.	LE32-3MAFQ	2NTK1	35.85
32	150	1 Gal.	LE32-3MAF1	2NTK2	106.30
32	150	5 Gal.	LE32-3MAF5	2NTK3	507.50
68	300	1 Gal.	LE68H1	1K465	154.25
68	300	5 Gal.	LE68H5	1K461	728.50
AB Alkylbenzene Lubricants					
32	150	1 Gal.	LAB151	1K497	56.10
46	200	1 Gal.	LAB201	1K491	68.40
68	300	1 Gal.	LAB301	1K485	62.20
Mineral Lubricants					
32	150	1 Gal.	L318	2W277	26.70
32	150	5 Gal.	L321	4E842	135.30
68	300	1 Gal.	L319	2W278	30.05
68	300	5 Gal.	L322	4E843	154.75
Oil Pump					
—	—	—	VOP-H	3GA16	175.00

AB ALKYL BENZENE LUBRICANTS

OEM-approved for use with HCFCs, CFCs, and ammonia refrigerants. Low floc points and pour point. Low foaming characteristics.

MINERAL LUBRICANTS

Napthenic-based mineral oils. Low wax content and low pour point.

OIL PUMP

Mounts on 1- and 5-gal. containers of refrigeration oil to pump directly into compressors. Max. pressure: 250 psi.



No. **1K467**



No. **1K497**



No. **2W277**