

Contact:

AirPro

Universal -use with any indoor fan with 1/8" IPS light kit adapter • Dry Location Listed



Description:

Four-light universal fan light kit features alabaster style glass shades beautiful in design. Brushed Nickel finish corresponds with a Chrome pull-chain and maple fob. Universal style for use with fans that accept an accessory light comes with quick-connect wiring. Includes four 3000K, 800 lumen each (source), Title 24 certified LED bulbs.

Specifications:

- · Alabaster glass Shade
- · Add style and light to your ceiling fan with this universal fan light kit.
- · Alabaster style glass shades
- · Chrome pull chain w/ maple fob
- · Quick-connect wiring to any progress fan that accept an accessory light.
- · Includes four 3000K, 800 lumen each (source), Title 24 certified LED bulbs
- · Energy Star Qualified
- · Meets California T24 JA8-2016.
- · Fully dimmable with dimmable bulbs.
- 6 in of wire supplied

Performance:

Number of Lamps	4
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	800/88 (LM-82)
ССТ	3000 K
CRI	90 CRI
Life (hours)	25000 (L70/TM-21)
EMI/RFI	Title 24
Max. Operating Temp	40 °C
Warranty	1-year Limited Warranty
Labels	UL Dry Location Listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016


P2643-09WB



Dimensions:

Diameter: 13-3/4 in Height: 8 in

Alabaster glass Shade Width: 5-3/8 in Height: 4-7/8 in





AirPro

Universal -use with any indoor fan with 1/8" IPS light kit adapter • Dry Location Listed



Dimming Notes:

P2643-09WB is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Lutron_Nova T NTELV-300

Lutron_Maestro MAELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P2643-09WB