

Project Name

Location

Prepared By



SATCO S39392

36W/LED/HID/5000K/100-277V E26

Notes

[www] 11-09-2020 01:10:24

General

| | |
|-------------------------|---|
| Status | Active |
| Watts | 36 |
| Incandescent Equivalent | 200 |
| Fluorescent Equivalent | 55 |
| HID Equivalent | 150 |
| Volts | 100V-277V |
| Shape | Comcob |
| Base | Medium |
| ANSI Base | E26 |
| Finish | Clear |
| CCT (Kelvin) | 5000 |
| Temperature | Natural Light |
| CRI | 80 |
| Lumens | 5148 |
| Beam Spread | 300 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Comcob |
| Technology | LED |
| Min Compartment Size | Length: 6 in. Width: 8.5 in. Depth: 6 in. |
| Ballasting Requirements | Ballast Bypass-Direct wire only 100-277V |

Electrical

| | |
|-----------------------|--|
| Working Voltage | AC 90-305V |
| Operating Frequency | 50/60 Hz |
| Power Factor | >0.9 |
| Burning Position | Universal |
| Surge Protection | Built-in surge protection - 4KV |
| Operating Temperature | -25C (-13F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|---------|
| MOL | 7.34 |
| MOD | 3.34 |
| Lens Finish | Clear |
| Lens Material | Plastic |
| Housing Color | White |
| Weight (lb.) | 1.52 |

Additional Information

| | |
|----------------------------|---|
| Additional Info | UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) |
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP64 |
| Shatter-Proof Type | Shatter resistant materials. Acceptable for use in food prep areas |

Warranty

5 Year Limited - Hi-Pro

Compliance

| | |
|-----------------|-------------------------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

