SATCO NUVO

Project Name

Location

Prepared By



SATCO S39393

45W/LED/HID/5K/100-277V/EX39

Notes

[www] 11-09-2020 01:16:

For More Information Visit:

https://www.satco.com/

General	
Ctatue	Activo
Status	Active
Watts	45
Incandescent Equivalent	300
Fluorescent Equivalent	65
HID Equivalent	175
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI .	80
Lumens	6435
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 11 in. Width: 8 in. Depth: 8 in.
Ballasting Requirements	Ballast Bypass-Direct wire only 100- 277V
Electrical	
Working Voltage	AC 100-277V
Working Voltage Operating Frequency	AC 100-277V 50/60 Hz
Operating Frequency	50/60 Hz
Operating Frequency Power Factor	50/60 Hz >0.9
Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Operating Frequency Power Factor Burning Position Surge Protection	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic White 1.85 Approved for totally enclosed fixtures; Base up, base down or horizontal operation; For outdoor & indoor use; Emits no UV light /
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.81 3.34 Clear Plastic White 1.85 Approved for totally enclosed fixtures; Base up, base down or horizontal operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)

Warranty 5 Year Limited - Hi-Pro Compliance Safety Listing cULus Location Rating Damp Energy Star No DLC Approved Yes DLC ID PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Lamp		areas	
Safety Listing cULus Location Rating Damp Energy Star No DLC Approved Yes DLC ID PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	Warranty	5 Year Limited - Hi-Pro	
Location Rating Energy Star DLC Approved PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	Compliance		
Energy Star DLC Approved PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	Safety Listing	cULus	
DLC Approved Yes DLC ID PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	Location Rating	Damp	
DLC ID PL271RHFVSJW CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	Energy Star	No	
CEC Status Lawful for sale in California RoHS Compliant Yes FCC Compliant Yes	DLC Approved	Yes	
RoHS Compliant Yes FCC Compliant Yes	DLC ID	PL271RHFVSJW	
FCC Compliant Yes	CEC Status	Lawful for sale in California	
	RoHS Compliant	Yes	
SDS Sheet LED_Lamp	FCC Compliant	Yes	
	SDS Sheet	LED_Lamp	





