



S29916

14T8/LED/48-850/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 5000K; 50000 Average
 rated hours; 1800 lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29916

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

| Item Number | UPC | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Lamp Shape | Base |
|----------------|-----------------------------|--|--------------------------------|---------------------|------------------------|-------------------------------|--|
| S29916 | 045923299162 | 120-277 | 14 | 50/60Hz | 25W-32W | T8 | Medium Bi-Pin |
| ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours |
| G13 | 14T8/LED/48-850/BP 120-277V | Non-Dimmable | White | 48" | 1.00" | 1800 | 50000 |
| Kelvin Temp | Color | CRI | Beam Spread Deg | Pack | Package Type | CEC Status | DLC ID: |
| 5000 | Natural Light | 82 | 210 | 25 | Box | Lawful for sale in California | PLZBOEH3B9H7 DLC Search |
| RoHS Compliant | UL or ETL Listed | UL Classification | Warranty | | | | |
| Yes | Yes | cULus Classified - Damp Location Rated | 5 Year Limited | | | | |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

