Uponor AquaPEX[®] White, Straight Lengths

Submittal Information Revision B: July 23, 2009

Project Information

Job Name: Location: Part No. Ordered: Engineer: Date Submitted: Contractor: Submitted By: Manufacturer's Representative: Approved By: Technical Data Image: Contractor:

Material:	Crosslinked polyethylene PEX-a Engel Method; PEX 5006		
Standard Grade Hydrostatic Ratings (PPI):	200°F (93°C) at 80 psi 180°F (82°C) at 100 psi 73.4°F (23°C) at 160 psi ½",¾" and 1" AquaPEX [®] White tubing only: 120°F (49°C) at 130 psi		
Linear Expansion Rate:	1.10"/10°F (12°C)/100'		

Product Information and Application Use

Uponor AquaPEX White straight length tubing is used primarily in hot and cold potable water distribution systems and AQUASAFE[™] Residential Fire Safety systems.

\checkmark	Description	Part Number	Α	В	Weight
	1/2" Uponor AquaPEX White, 20-ft. straight lengths, 500 ft.	F1930500	0.475"	0.625"	28.0 lbs.
	3/4" Uponor AquaPEX White, 20-ft. straight lengths, 300 ft.	F1930750	0.671"	0.875"	31.0 lbs.
	1" Uponor AquaPEX White, 20-ft. straight lengths, 200 ft.	F1921000	0.862"	1.125"	35.0 lbs.
	1 ¹ / ₄ " Uponor AquaPEX White, 20-ft. straight lengths, 100 ft.	F1921250	1.054"	1.375"	32.0 lbs.
	11/2" Uponor AquaPEX White, 20-ft. straight lengths, 100 ft.	F1921500	1.244"	1.625"	42.0 lbs.
	2" Uponor AquaPEX White, 20-ft. straight lengths, 100 ft.	F1922000	1.629"	2.125"	68.15 lbs.

B

Installation

Approved fittings are ProPEX[®] fittings.¹ Refer to the AquaPEX Professional Plumbing Installation Handbook or AQUASAFE Fire Safety Installation Guide for additional information.

Standards

CSA B137.5; ASTM F876; ASTM F877; ASTM F1960; ASTM-E84; ASTM-E119/UL 263

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

*½", ¾", 1" UL 1821; *ULC/ORD - C 199 P; IAPMO; CSA; HUD; WARNOCK HERSEY; NSF; ITS; UL; ICC; ANSI/NSF 14- and 61-certified; CAN/ULC S102.2; U.S.: ¾" diameter and smaller; Canada: 1" diameter and smaller

Related Applications

PEX-a Plumbing Systems AQUASAFE Residential Fire Safety Systems

Contact Information

Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Fax: (952) 891-2008 www.uponor-usa.com Uponor Ltd. 2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca

uponor

¹ProPEX[®] is a registered trademark of Uponor, Inc. ProPEX^m is a trademark of Uponor Ltd.