

SPECIFICATION SHEETS

WLLED48

COBRA LOW PROFILE WRAP AROUND



NAME:	
TYPE:	
DATE:	
NOTES:	

SPECIFICATIONS

WIRING:	Hardwire only. Installs easily in traditional junction boxes (3" or 4"). Also features an internal junction box when the application requires linking multiple units in series.
HOUSING DETAILS:	Metal housing with durable plastic end caps. Mounts flush to a wall or ceiling.
OPTICS:	LED strip technology uses a light guided reflector to distribute light and optimize high level of delivered lumens. Integrated LED - no bulbs required. Maintenance free LED ceiling light.
ELECTRICAL:	Easily connected to a 120-277V power supply via provided UL recognized driver. NON-IC and DAMP LOCATIONS rated.
	Certifications : This product is ETL and Energy Star listed in USA and Canada.
LENS:	A light guide reflector in combination with a white acrylic frosted lens, provides an even light distribution.

COLOR TEMPERATURE:	4k
CRI:	80+
LUMEN OUTPUT:	4000 lumens
DIMMABLE:	No
WATTS:	40W
LED LIFE:	50,000 hours
WARRANTY:	5 years
VOLTAGE:	120-277V
HEIGHT:	2.6" (6.60 cm)
LENGTH:	47.4" (120.40 cm)
WIDTH:	5.5" (13.97 cm)
INTEGRATED MOTION SENSOR:	No

APPLICATIONS


Low-profile LED wrap around with a frosted diffuser providing a widespread, uniform illumination. Ideal for many applications, including corridors, laundry rooms, kitchens, break rooms, utility work areas and stairways. Ideal for interior ceiling or wall installations in residential or commercial applications.



WLLED48

COBRA LOW PROFILE WRAP AROUND

DIMENSIONS



RATINGS







ORDERING GUIDE

COBRA WRAP LIGHT SERIES

 Series
 Length
 Color Temperature
 Finish

 WLLED
 48
 4K 4000K/80CRI/40W
 WH White

Notes: Configure product using BOLD options: Ex: WLLED48-4K-WH