

GP6500

GP SERIESPortable Generator

Features

- CO-SENSE™ Technology STOPS, ALERTS, SAVES. Powerful protection against hazardous carbon monoxide.
- PowerRush™ Advanced Technology delivers up to 40% more starting capacity allowing you to do more with less.*
- Generac's OHV engine with splash lubrication provides a long engine life.
- Low-oil level shutdown automatically safeguards engine from damage.
- Large-capacity steel fuel tank with incorporated fuel gauge provides durability and up to a 10.5 hour run-time at 50% load.
- 1 1/4" **steel-tube cradle** for added durability and strength.
- Hour Meter tracks maintenance intervals.
- Heavy-duty, never-flat wheels allow for easy portability.
- Fold-down handle for sturdy portability and compact storage.

*Increases electrical current upon demand; above rated output when starting electric motors

Model 7680-0 UPC: 696471075120

(49-State)


Model 7683-0 UPC: 696471075137

(50-State)



AC Rated Output Running Watts 6500 AC Maximum Output Starting Watts 8125

Control Panel





GENERAC°

Specifications

GP6500

CDGF00
GP6500
7680-0 / 7683-0
49 ST / 50 ST
6500
8125
120/240 VAC
60 Hz
54.2 / 27.1
389cc
OHV
3600
10W-30 / SAE 30
1.06 (1.0)
Splash
Yes
On Engine
On Fuel Tank
Recoil Pull Start
Yes

Neutral Bonded to Ground	Yes
Start Switch Type	On / Off
Start Switch Location	On Control Panel
Fuel Gauge	Yes
Fuel Tank Capacity gal (L)	6.9 (26)
Run Time at 50% of Rated Load (Hours)	10.5
Handle Style	Dual Grip, Single Folding with Lock Pin
Wheel Type	9.5" Never Flat
Warranty- Residential	3 Year Limited
Warranty- Commercial	1 Year Limited
Included	engine oil, oil funnel, handle & wheel kit, owner's manual

Dimensions and Weights

Length in (mm)	27.2 (692)
Width in (mm)	27 (684)
Ext. Length in (mm)	45.3 (1151)
Height in (mm)	26.5 (674)
Carton Length in (mm)	28.3 (720)
Carton Width in (mm)	21.7 (550)
Carton Height in (mm)	28 (710)
Unit Weight lbs (kg)	172 (78)
Shipping Weight lbs (kg)	196 (88.9)

