

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WELD-ON® C-65™ Low VOC Cleaner for Plastic Pipe
PRODUCT USE: Low VOC Cleaner for Plastic Pipe (PVC, CPVC, ABS and Styrene)
SUPPLIER: **MANUFACTURER:** IPS Corporation
 17109 South Main Street, Gardena, CA 90248-3127
 P.O. Box 379, Gardena, CA 90247-0379
 Tel. 1-310-898-3300
EMERGENCY: Transportation: CHEMTEL Tel. 800-255-3924, +1 813-248-0585 (International) **Medical:** CHEMTEL Tel. 800-255-3924, +1 813-248-0585 (International)

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Acute Toxicity: Health Category 4 Skin Irritation: Category 3 Skin Sensitization: NO Eye: Category 2B	Acute Toxicity: Environmental None Known Chronic Toxicity: None Known	Flammable Liquid Physical Category 2
--	--	--------------------------------------

GHS LABEL: **Signal Word:** Danger **WHMIS CLASSIFICATION:** CLASS B, DIVISION 2

<p style="text-align: center;"><u>Hazard Statements</u></p> H225: Highly flammable liquid and vapor H319: Causes serious eye irritation H336: May cause drowsiness or dizziness EUH 066: Repeated exposure may cause skin dryness or cracking.	<p style="text-align: center;"><u>Precautionary Statements</u></p> P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking P261: Avoid breathing dust/fume/gas/mist/vapors/spray P280: Wear protective gloves/protective clothing/eye protection/face protection P337+P313: Get medical advice/attention P403+P233: Store in a well ventilated place. Keep container tightly closed P501: Dispose of contents/container in accordance with local regulation
---	---

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS #	REACH		CONCENTRATION % by Weight
			Pre-registration Number		
Acetone	67-64-1	200-662-2	05-2116297713-35-0000		75 - 100
Cyclohexanone	108-94-1	203-631-1	05-2116297718-25-0000		2 - 15

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.
 * Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).
 # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.
Likely Routes of Exposure: Inhalation, Eye and Skin Contact
Acute symptoms and effects:
Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
Eye Contact: Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.
Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.
Ingestion: May cause nausea, vomiting, diarrhea and mental sluggishness.
Chronic (long-term) effects: Defatting dermatitis with prolonged use. In humans, passes the placental barrier, detected in maternal milk. (Based on Acetone)

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical powder, carbon dioxide gas, foam, Halon, water fog. HMIS NFA 0-Minimal
Unsuitable Extinguishing Media: Water spray or stream. Health 2 1-Slight
Exposure Hazards: Inhalation and dermal contact Flammability 3 3 2-Moderate
Combustion Products: Oxides of carbon and smoke Reactivity 0 0 3-Serious
PPE B 4-Severe
Protection for Firefighters: Self-contained breathing apparatus or full-face positive pressure airline masks.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Keep away from heat, sparks and open flame.
 Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.
 Prevent contact with skin or eyes (see section 8).
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Clean up with sand or other inert absorbent material. Transfer to a closable steel vessel.
Materials not to be used for clean up: Aluminum or plastic containers

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing.
 Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.
 Do not eat, drink or smoke while handling.
Storage: Store in ventilated room or shade below 44°C (110°F) and away from direct sunlight.
 Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.
 Follow all precautionary information on container label, product bulletins and solvent cementing literature.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL	OSHA PEL-Ceiling	CAL/OSHA PEL	CAL/OSHA Ceiling	CAL/OSHA STEL
Cyclohexanone	20 ppm	50 ppm	50 ppm	50 ppm	N/E	N/E	25 ppm	N/E	N/E

Engineering Controls: Use local exhaust as needed.
Monitoring: Maintain breathing zone airborne concentrations below exposure limits.
Personal Protective Equipment (PPE):
Eye Protection: Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.
Skin Protection: Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.
 Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.
Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.
 With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, thin liquid		Odor Threshold: 0.88 ppm (Cyclohexanone)
Odor: Ketone		
pH: Not Applicable		Boiling Range: 56°C (133°F) to 156°C (313°F)
Melting/Freezing Point: -95°C (-139°F) Based on first melting component: Acetone		Evaporation Rate: > 1.0 (BUAC = 1)
Boiling Point: 56°C (133°F) Based on first boiling component: Acetone		Flammability: Category 2
Flash Point: -20°C (-4°F) T.C.C. based on Acetone		Flammability Limits: LEL: 1.1% based on Cyclohexanone
Specific Gravity: 0.794 @23°C (73°F)		UEL: 12.8% based on Acetone
Solubility: Solvent portion soluble in water.		Vapor Pressure: 190 mm Hg @ 20°C (68°F): Acetone
Partition Coefficient n-octanol/water: Not Available		Vapor Density: >2.0 (Air = 1)
Auto-ignition Temperature: 465°C (869°F): Acetone		Other Data: Viscosity: Water-thin
Decomposition Temperature: Not Applicable		
VOC Content: When applied as directed, per SCAQMD Rule 1171, VOC content is: ≤ 25 g/l.		

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable
Hazardous decomposition products: None in normal use. When forced to burn, this product gives off oxides of carbon and smoke.
Conditions to avoid: Keep away from heat, sparks, open flame and other ignition sources.
Incompatible Materials: Oxidizers, strong acids and bases, amines, ammonia

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicity:	LD ₅₀	LC ₅₀
Acetone	Oral: 5800 mg/kg (rat)	Inhalation 50,100 mg/m3 (rat)
Cyclohexanone	Oral: 1535 mg/kg (rat), Dermal: 948 mg/kg (rabbit)	Inhalation 4 hrs. 8,000 PPM (rat)

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: None Known
Mobility: In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of ≤ 25 g/l.
Degradability: Readily Biodegradable
Bioaccumulation: Minimal to none.

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name: Flammable Liquid, n.o.s. (Acetone)	
Hazard Class: 3	EXCEPTION for Ground Shipping
Secondary Risk: None	DOT Limited Quantity: Up to 1L per inner packaging, 30 kg gross weight per package.
Identification Number: UN 1993	Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D" .
Packing Group: PG II	
Label Required: Class 3 Flammable Liquid	
Marine Pollutant: NO	

TDG INFORMATION	
TDG CLASS:	FLAMMABLE LIQUID 3
SHIPPING NAME:	Flammable Liquid, n.o.s. (Acetone)
UN NUMBER/PACKING GROUP:	UN 1993, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information: Highly Flammable, Irritant	Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia	
Symbols: F, Xi	AICS, Korea ECL/TCCL, Japan MITI (ENCS)	
Risk Phrases: R11: Highly flammable. R36/37: Irritating to eyes and respiratory system.	R66: Repeated exposure may cause skin dryness or cracking R67: Vapors may cause drowsiness and dizziness	
Safety Phrases: S2: Keep out of the reach of children S9: Keep container in a well-ventilated place. S16: Keep away from sources of ignition - No smoking.	S25: Avoid contact with eyes. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33: Take precautionary measures against static discharges.	

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	IPS, Safety Health & Environmental Affairs	All ingredients are compliant with the requirements of the European
E-mail address:	<EHSinfo@ipscorp.com>	Directive on RoHS (Restriction of Hazardous Substances).
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	4/7/2015 / Updated GHS Standard Format	
Intended Use of Product:	Cleaner for Plastic Pipe (PVC, CPVC, ABS and Styrene)	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.