

ABS Foam Core Pipe

ABS Schedule 40 DWV Pipe (For Non-Pressure Applications)



ABS SCHEDULE 40 FOAM CORE (BLACK)			PLAIN END		ASTM F 628	
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	WT. PER 100 FT. (LBS.)
ABS 3112	1½" x 10'	03132	2590	1.900	0.145	27.1
ABS 3112	1½" x 20'	03133	5180	1.900	0.145	27.1
ABS 3200	2" x 10'	03134	1670	2.375	0.154	37.7
ABS 3200	2" x 20'	03135	3340	2.375	0.154	37.7
ABS 3300	3" x 10'	03136	750	3.500	0.216	74.5
ABS 3300	3" x 20'	03137	1500	3.500	0.216	74.5
ABS 3400	4" x 10'	03138	480	4.500	0.237	107.1
ABS 3400	4" x 20'	03139	960	4.500	0.237	107.1
ABS 3600	6" x 20'	03141	400	6.625	0.280	187.8

NSF Listed. Meets All Requirements of ASTM F 628.



NOTICE

NOT FOR PRESSURE

Do not use PVC / ABS / ABS Plus® cellular core (foam core) pipe for pressure applications. The use of cellular core pipe in pressure applications may result in system failure and property damage.

WARNING

Testing with or use of compressed air or gas in PVC / ABS / CPVC pipe or fittings can result in explosive failures and cause severe injury or death.

AIR/GAS



- NEVER test with or transport/store compressed air or gas in PVC / ABS / CPVC pipe or fittings.
- NEVER test PVC / ABS / CPVC pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use PVC / ABS / CPVC pipe or fittings for water or approved chemicals.
- Refer to warnings on PFFA's website and ASTM D 1785.