



# HANGING STRAP

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development.

## FEATURES

- Lightweight
- Low cost
- High Strength Design
- Easy Installation
- Helps Eliminate Rattling
- Supports Flexible Duct Without Damaging
- Outer Jacket
- Resistant to Grease, Oil, Gasoline & Acid
- Waterproof & Airtight

## DESIGNED FOR HANGING

- Flexible Duct
- PVC Vent Duct
- Duct Board Systems
- Many Lighter Weight Steel
- Duct Applications

Fasten Strap  
To Beams



For maximum strength: put the two ends together and fold it over before securing to the ceiling or joist.



	VINYL DURO STRAP	NOVA STRAP
<b>FLAME SPREAD &amp; SMOKE DEVELOPMENT:</b>	NFPA Class A* UBC Class 1*	Less Than 25 / Less Than 50
<b>TENSILE STRENGTH:</b>	Warp-70 lbs./In. Fill-70 lbs./In	Warp-70 lbs./In.; Fill-70 lbs./In
<b>HEAT RESISTANCE:</b>	200° F	200° F
<b>TEAR STRENGTH:</b>	Warp- 8 lbs./In. Fill-11 lbs./In	N/A
<b>FABRIC:</b>	Black vinyl coated polyester fill	Black Woven Polypropylene
<b>TOTAL FABRIC THICKNESS:</b>	.022" Approx.	.025" Approx.
<b>QUANTITY PER CARTON:</b>	10 rolls (Conveniently packaged in a dispenser box with cutting blade)	24 rolls per box
<b>ADDITIONAL INFO:</b>	*Product Meets NFPA Class A and UBC Class 1 characteristics of flame spread less than 25 and smoke development less than 50 when utilizing test method ASTM E-84.	Resistant to Grease, Oil, Gasoline and Acid.

## Ordering Information

Item #	Code	Description	Quantity
10190	VDS200	Vinyl Duro Strap 1-1/2" x 200'	200 ft. Roll
10179	SVDS300	Single Sided Vinyl Duro Strap 1-1/2" x 300'	300 ft. Roll
10191	VDS3-200B	Vinyl Duro Strap 3" x 200'	200 ft. Roll
10180	NS300	Nova Strap 1-3/4" x 300'	300 ft. Roll

### Best Installation Practices

The Air Duct Council recommends supporting flex duct at manufacturers recommended intervals or no greater than 4'. Maximum centerline sag shall be no more than 1/2" per foot. Hanging Strap must be a minimum of 1-1/2" wide. For more information, please visit the Air Duct Council "Supporting Flexible Duct" section 4.6.



Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346  
 Duro Dyne Midwest Division, Hamilton, OH 513-870-6000 Fax: 513-870-6005  
 Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778  
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328  
 www.durodyne.com E-mail: durodyne@durodyne.com



© Duro Dyne Corp.  
 Printed in USA 9/17  
 BC008406