

Test Tools HVACR Pros Trust



SC260 Specs

Function	Range	Best Accuracy/ Best Resolution
Volts AC	600	1.2%±3 / 0.001
Amps AC	400	2.0%±10 / 0.01
Volts DC	600	0.5%±2 / 0.001
Ohms	40M	1.0%±5 / 0.01
Microfarads	4000	3%±5 / 0.001
°F	-30°F to 752°F	±1°F / 0.1
Battery	9V, 150 hrs Typical Alkaline	

* System accuracy (SC260 meter + Type K thermocouple after field calibration)

Compact Clamp Meter

Model SC260

Compact Clamp Meter

Model SC260



Test Tools HVACR Pros Trust

SC260



Suitable replacement for model SC53

HVACR Features

View True RMS measurements of HVACR electrical equipment on a backlit display, hang it hands-free, or even measure temperature.

Electrical Testing for HVACR

True RMS readings through the clamp or leads. Inrush current for starting amps.

Rugged Display Broad temperature range tolerance allows for testing in freezers and on rooftops.

Capacitance Test motor start and run capacitors.

Trusted Temps Reliable temperature in fast changing environments.

And More

- Magnetic hanger.
- Auto-check Diode, MFD, Ohms, or continuity.
- Max/min, Hold.
- Hi-voltage warning.
- Non contact voltage.
- Continuity.
- Diode test.
- Easy temperature calibration.
- Low ohm range for motor windings.
- Read up to 400AAC.
- 0.01AAC resolution.
- Auto-Power-Off.
- 9V Battery.
- NIST traceable.

Temperature Solutions

Type K thermocouples slide directly into the meter, no adapter needed. Calibration pot is easy to access for quick field calibration.

RIGHT STUFF

Grab It
The clamp's claw grabs the wire you want to measure.

Compact Clamp Meter

SC260

TrueRMS
Magnet
Temp




DO MORE

Magnetic Hanger
Keeps your meter where you need it, up high and hands free.

Included:
SC260 Clamp Meter
ATB1 Thermocouple
ADLS2 Silicone Leads
ANC4 Padded Case



Test Tools HVACR Pros Trust
www.fieldpiece.com



Watch the Video!

© Fieldpiece Instruments, Inc. 2014