

DIELECTRIC UNIONS - C X IP 



- Prevent Electrolysis or Galvanic action when connecting dissimilar metals
- Zinc Plated Forged Steel Body
- Female IPS Threads
- Brass Sweat Connection for Copper Pipe
- ABS Fiber Sleeve Separates Steel and Brass Components.
- Max Temperature: 210° F
- Max Pressure: 125 psi
- LEAD-FREE COMPLIANT.

Item No	Size	Std. Pkg	Price / Ea
1566A-LF	1/2" CWT x 1/2" FIP	1 Ea	
1567-LF	1/2" CWT x 3/4" FIP	1 Ea	
1568-LF	3/4" CWT x 3/4" FIP	1 Ea	
1569-LF	1" CWT x 1" FIP	1 Ea	
1573-LF	1-1/4" CWT x 1-1/4" FIP	1 Ea	
1574-LF	1-1/2" CWT x 1-1/2" FIP	1 Ea	
1576-LF	2" CWT x 2" FIP	1 Ea	



WASHERS FOR C X IP DIELECTRIC UNIONS

- Replacement Washers

Item No	Size	Std. Pkg	Price / 100
1566A-W	1/2" CWT x 1/2" FIP	1 Ea	
1567-W	1/2" CWT x 3/4" FIP	1 Ea	
1568-W	3/4" CWT x 3/4" FIP	1 Ea	
1569-W	1" CWT x 1" FIP	1 Ea	
1573-W	1-1/4" CWT x 1-1/4" FIP	1 Ea	
1574-W	1-1/2" CWT x 1-1/2" FIP	1 Ea	
1576-W	2" CWT x 2" FIP	1 Ea	



DIELECTRIC BUSHINGS

- Nylon Material
- Heavy Hexagon Shoulders
- Tapered M/F Iron Pipe Threads

- When installing use a good pipe sealant.
- Do not use with heat generating equipment.
- Max Temperature: 210° F
- Max Pressure: 125 psi working pressure

Item No	Size	Std. Pkg	Price / Ea
1612	1-1/4" MIP x 1" FIP	1 Ea	
1616	2" MIP x 1-1/2" FIP	1 Ea	
1618	2-1/2" MIP x 2" FIP	1 Ea	


DIELECTRIC UNIONS - IP X IP



- Cadmium Plated Malleable Iron Body
- Female IPS Threads
- Nylon Dielectric Element is permanently molded to the union body
- Recommended for water, oil & gas
- Max Temperature 210° F
- Max Pressure: 125 psi
- LEAD-FREE COMPLIANT.

Item No	Size	Std. Pkg	Price / Ea
1592	3/4" IP x 3/4" IP	1 Ea	
1593	1" IP x 1" IP	1 Ea	
1594	1-1/4" IP x 1-1/4" IP	1 Ea	
1595	1-1/2" IP x 1-1/2" IP	1 Ea	
1596	2" IP x 2" IP	1 Ea	

DIELECTRIC COUPLINGS



- Provides dielectric protection from corrosion between dissimilar metal piping.
- Inner Dielectric Element is a Threaded Thermosetting Plastic Laminate.
- Cadmium Plated Steel Body
- Recommended for use with fresh water and petroleum products.
- Do not use with salt water.
- Max Temperature: 210° F
- Max Pressure: 125 psi

Item No	Size	Std. Pkg	Price / Ea
1578	1/2" FIP	12 Ea	
1579	3/4" FIP	12 Ea	
1580	1" FIP	1 Ea	
1581	1-1/4" FIP	1 Ea	
1582	1-1/2" FIP	1 Ea	
1583	2" FIP	1 Ea	
1584	2-1/2" FIP	1 Ea	
1585	3" FIP	1 Ea	



PRODUCTS MEET THE STRICT LEAD-FREE STANDARDS OF THE SAFE DRINKING WATER ACT.