

# Connected Thermostats

## Wi-Fi 9000 Color Touchscreen



Honeywell's Wi-Fi 9000 allows remote access to the thermostat through a computer, tablet, or smartphone with Honeywell's Total Connect Comfort Service.

- Tri-lingual - English, French and Spanish display options.
- Get Connected – Connect to home's existing Wi-Fi network
- Remote Control – Convenience, comfort and control from anywhere through web, tablet or smartphone access
- Apps available for tablet and smartphones
- Automatic software updates through Wi-Fi
- Selectable to 7 Day or Non-Programmable
- Program thermostat locally or over the web or app
- Customize the screen color to match any décor

**Applications:** Up to 3 Heat/2 Cool Heat Pumps; Up to 2 Heat/2 Cool Conventional Systems

**Display:** Color Touchscreen

**Display Size:** 8.06 sq in.

**Mounting:** Horizontal

**Color:** Premier White®

**Changeover:** Auto or Manual

**Stages:** Up to 3 Heat/2 Cool Heat Pump; Up to 2 Heat/2 Cool Conventional

**Scheduling:** On-line scheduling or Locally at thermostat

**Switch Positions (System):** HEAT-OFF-COOL-AUTO-EM.HEAT

**Switch Positions (Fan):** AUTO-ON-CIRC-FOLLOW SCHEDULE

**Setting Temperature Range:** Heat: 40°F to 90°F; Cool: 50°F to 99°F (Heat: 4.5°C to 32°C; Cool: 10°C to 37°C)

**Operating Temperature Range:** 32°F to 120°F (0°C to 48.9°C)

**Operating Humidity Range (% RH):** 5 to 90% RH, non-condensing

**Power Method:** Hardwired

**Supply Voltage:** 18 to 30 Vac

**Frequency:** 50 Hz; 60 Hz

**Electrical Ratings:** 18 to 30 Vac

**Dimensions:** 3 1/2 in. High, 4 1/2 in. Wide, 7/8 in. Deep (88 mm. High, 115 mm. Wide, 22 mm. Deep)

**Used With:** THP9045 Wire Saver

**Comments:** Tri-Lingual Display (selectable for English, French or Spanish)

**Accessories:**

**THP9045A1023/U – WireSaver**

Material Number	Programmability	Terminal Designations
TH9320WF5003/U	7-Day Multiple Day Programming or Non-Programmable	R, RC, C, W (O/B), W2 (AUX/E), Y, Y2, G, L, K

## Wi-Fi VisionPRO® 8000



Your customers want comfort, convenience and connectivity.

With the Wi-Fi VisionPRO, you can offer them all three. Using an existing Wi-Fi network plus Honeywell's free Total Connect Comfort services, the Wi-Fi VisionPRO allows homeowners to remotely control their comfort settings and manage their energy costs – with ease.

- Intuitive programming for easier setup
- Remote comfort control via computer, tablet or smartphone
- Universal application across more system types
- Equipment check/change reminders
- Programmable for annual energy savings

**Applications:** Up to 3 Heat/2 Cool heat pump or up to 2 Heat/2 Cool conventional

**Display Size:** 10 sq in.

**Color:** Arctic White

**Changeover:** Auto or Manual

**Stages:** Up to 3 Heat / 2 Cool Heat Pump or Up to 2 Heat / 2 Cool Conventional

**Switch Positions (System):** HEAT-OFF-COOL-AUTO-EM.HEAT

**Switch Positions (Fan):** AUTO-ON-CIRC-FOLLOW SCHEDULE

**Setting Temperature Range:** Heat: 40°F to 90°F; Cool 50°F to 99°F (Heat: 4.5°C to 32.0°C; Cool: 10°C to 37.0°C)

**Operating Temperature Range:** 32°F to 120°F (0°C to 48.9°C)

**Humidification Setting Range:** Cooling: 40 to 80% RH. Heating: 10 to 60% RH.

**Dehumidification Setting Range:** 40 to 80% RH.

**Operating Humidity Range (% RH):** 5 to 90% RH, non-condensing

**Power Method:** Hardwired

**Supply Voltage:** 18 to 30 Vac or 750 mV

**Frequency:** 50 Hz; 60 Hz

**Electrical Connections:** Screw terminals

**Electrical Ratings:** 18 to 30 Vac or 750 mV

**Dimensions:** 4 5/8 in. High, 4 15/16 in. Wide, 1 1/8 in. Deep (118 mm. High, 126 mm. Wide, 29 mm. Deep)

**Includes:** Wi-Fi VisionPRO® 8000 thermostat

**Accessories:**

**THP9045A1023/U – WireSaver**

Material Number	Programmability	Terminal Designations
TH8321WF1001/U	7-Day Multiple Day Programming or Non-Programmable	R, RC, C, W-O/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1 U1, S1 S1

# Programmable Commercial Thermostats

## Wi-Fi 9000 Color Touchscreen



**Applications:** Up to 3 Heat/2 Cool Heat Pumps; Up to 2 Heat/2 Cool Conventional Systems  
**Display:** Color Touchscreen  
**Display Size:** 8.06 sq in.  
**Mounting:** Horizontal  
**Color:** Premier White®  
**Changeover:** Auto or Manual  
**Stages:** Up to 3 Heat/2 Cool Heat Pump; Up to 2 Heat/2 Cool Conventional  
**Scheduling:** On-line scheduling or Locally at thermostat  
**Switch Positions (System):** HEAT-OFF-COOL-AUTO-EM.HEAT  
**Switch Positions (Fan):** AUTO-ON-CIRC-FOLLOW SCHEDULE  
**Setting Temperature Range:** Heat: 40°F to 90°F; Cool: 50°F to 99°F (Heat: 4.5°C to 32°C; Cool: 10°C to 37°C)

Honeywell's Wi-Fi 9000 allows remote access to the thermostat through a computer, tablet, or smartphone with Honeywell's Total Connect Comfort Service.

- Tri-lingual - English, French and Spanish display options.
- Get Connected – Connect to home's existing Wi-Fi network
- Remote Control – Convenience, comfort and control from anywhere through web, tablet or smartphone access
- Apps available for tablet and smartphones
- Automatic software updates through Wi-Fi
- Selectable to 7 Day or Non-Programmable
- Program thermostat locally or over the web or app
- Customize the screen color to match any décor

**Operating Temperature Range:** 32°F to 120°F (0°C to 48.9°C)  
**Operating Humidity Range (% RH):** 5 to 90% RH, non-condensing  
**Power Method:** Hardwired  
**Supply Voltage:** 18 to 30 Vac  
**Frequency:** 50 Hz; 60 Hz  
**Electrical Ratings:** 18 to 30 Vac  
**Dimensions:** 3 1/2 in. High, 4 1/2 in. Wide, 7/8 in. Deep (88 mm. High, 115 mm. Wide, 22 mm. Deep)  
**Used With:** THP9045 Wire Saver  
**Comments:** Tri-Lingual Display (selectable for English, French or Spanish)

**Accessories:**  
**THP9045A1023/U – WireSaver**

Material Number	Programmability	Terminal Designations
TH9320WF5003/U	7-Day Multiple Day Programming or Non-Programmable	R, RC, C, W (O/B), W2 (AUX/E), Y, Y2, G, L, K

## Wi-Fi VisionPRO® 8000



**Applications:** Up to 3 Heat/2 Cool heat pump or up to 2 Heat/2 Cool conventional  
**Display Size:** 10 sq in.  
**Color:** Arctic White  
**Changeover:** Auto or Manual  
**Stages:** Up to 3 Heat / 2 Cool Heat Pump or Up to 2 Heat / 2 Cool Conventional  
**Switch Positions (System):** HEAT-OFF-COOL-AUTO-EM.HEAT  
**Switch Positions (Fan):** AUTO-ON-CIRC-FOLLOW SCHEDULE  
**Setting Temperature Range:** Heat: 40°F to 90°F; Cool 50°F to 99°F (Heat: 4.5°C to 32.0°C; Cool: 10°C to 37.0°C)  
**Operating Temperature Range:** 32°F to 120°F (0°C to 48.9°C)  
**Humidification Setting Range:** Cooling: 40 to 80% RH. Heating: 10 to 60% RH.

Your customers want comfort, convenience and connectivity. With the Wi-Fi VisionPRO, you can offer them all three. Using an existing Wi-Fi network plus Honeywell's free Total Connect Comfort services, the Wi-Fi VisionPRO allows homeowners to remotely control their comfort settings and manage their energy costs – with ease.

- Intuitive programming for easier setup
- Remote comfort control via computer, tablet or smartphone
- Universal application across more system types
- Equipment check/change reminders
- Programmable for annual energy savings

**Dehumidification Setting Range:** 40 to 80% RH.  
**Operating Humidity Range (% RH):** 5 to 90% RH, non-condensing  
**Power Method:** Hardwired  
**Supply Voltage:** 18 to 30 Vac or 750 mV  
**Frequency:** 50 Hz; 60 Hz  
**Electrical Connections:** Screw terminals  
**Electrical Ratings:** 18 to 30 Vac or 750 mV  
**Dimensions:** 4 5/8 in. High, 4 15/16 in. Wide, 1 1/8 in. Deep (118 mm. High, 126 mm. Wide, 29 mm. Deep)  
**Includes:** Wi-Fi VisionPRO® 8000 thermostat

**Accessories:**  
**THP9045A1023/U – WireSaver**

Material Number	Programmability	Terminal Designations
TH8321WF1001/U	7-Day Multiple Day Programming or Non-Programmable	R, RC, C, W-O/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1 U1, S1 S1