


The ProPlus™ adjustable arc and continuous full-circle gear driven rotor comes standard with nine numerically coded interchangeable nozzles. Excellent nozzle performance delivers an exceptional fall out pattern. In independent testing by C.I.T., the ProPlus™ delivered up to 90% uniform coverage.

Tough, proven and advanced, the ProPlus™ is the leader in it's class. Set it and forget it. Arc Memory Clutch returns the rotor to its preset position. Technology works for you.



Easy Arc Setting

Arc Selection 40°
to Continuous 360°
Adjust From Left Start



Models

11003	ProPlus™
11003-HP	ProPlus™ (30,5 cm) 12" High Pop
11003-SH	ProPlus™ Shrub Head

OTHER OPTIONS: ADD TO PART NUMBER

-CV	Check Valve
-LA	Low Angle Nozzle
-NN	No Nozzle
-RCW	Reclaimed Water Use

Features and Benefits

- **Revolutionary Patented Top Arc Set** – Simplified arc set allows for wet or dry adjustment in seconds.
- **5" (12,7 cm) Riser** – Perfect for grasses with thick thatch.
- **3/4" (1,9 cm) Inlet** – Replaces all standard rotors.
- **2N1 Adjustable or Continuous Rotation** – Provides a full range adjustment from 40° to a continuous full circle.
- **Patented Arc Set Degree Markings** – Clearly indicates current watering pattern & simplifies arc set adjustment.
- **Arc Memory Clutch** – Prevents internal gear damage and returns rotor to its prior setting automatically if nozzle turret is forced past its stop.
- **Time Proven Patented Reversing Mechanism** – Assures continuous reverse and return...over a 35 year history.
- **Ratcheting Riser** – Allows for easy adjustment of your fixed starting position with a simple turn of the riser.
- **Rubber Cover** – Seals out dirt, increases product durability.
- **Wide Selection of Nozzles** – Including standard and low angle, provides flexibility in system design.
- **Optional Check Valve** – Prevents low head drainage.

Specifications

- Inlet: (1,9 cm) 3/4" Threaded NPT
- Arc Adjustment Range: 40° to Continuous 360°
- Flow Range: .5 – 10.0 GPM (1,9 – 37,8 LPM)
- Pressure Rating: 20 – 70 PSI (2 – 4,8 bars)
- Precipitation Rate: .12 – .89 in/hr (3 – 26 mm/hr) (Depending on Spacing and Nozzle Used)
- Overall Height (Popped Down): 7 1/2" (19 cm) (17" (43,2 cm) for High Pop Model)
- Recommended Spacing: 28' – 44' (8,5 – 13,2 m)
- Radius: 22' – 50' (6,7 – 15,3 m)
- Nozzle Trajectory: 26°
- Low Angle Nozzle Trajectory: 12°
- Standard and Low Angle Nozzles Included
- Riser Height: 5" (12,7 cm) and 12" (30,5 cm)

How to Specify

Model Number	Description
11003	-RCW