

# EASY-TWIST™

## Wire Connectors

### Standard Twist-On

#### WC Series



#### SPECIFICATIONS

- UL 486C Listed wire connector E155027.
- **Temperature Rating:** 105 °C (221 °F), 150 °C (302 °F) High Temp.
- **Voltage:** 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.
- **Example: (100) (10x100) = 100 in standard package, 1000 in standard carton.**

#### FEATURES

- Flame retardant UL 94V-2 thermoplastic shell provides excellent electrical insulation.
- Fixed, precise square wire spring provides secure gripping of conductors.
- Deep skirt entry provides protection from flashback and shorts.
- Sure-grip ribs improve gripping comfort.
- Compact design ensures proper installation, especially in tight spaces.
- Threaded funnel entry guides the wires into the connector easily.
- Pre-twisting of wires is not necessary.
- Zinc-plated springs for low contact resistance.
- **Installation:** Socket installation tools are included in each bag of Easy-Twist™ Connectors (Cat. No. with "B" suffix).  
Made to fit any pneumatic or electrical tool with a 1/4" chuck or drive socket.



EASY-TWIST™



COLOR/TYPE	CARTON	SMALL JAR	LARGE JAR	LARGE BAG	BULK	DRUM
Grey (WC)	WC-G-C (100) (10x100)	WC-G-SJ (300) (50x300)	—	WC-G-B (1000) (26x1000)	WC-G (25000)	—
Blue (WC)	WC-B-C (100) (10x100)	WC-B-SJ (300) (50x300)	—	WC-B-B (1000) (18x1000)	WC-B (10000)	—
Orange (WC)	WC-O-C (100) (10x100)	WC-O-CJ (100) (50x100)	WC-O-J (700) (12x700) WC-O-SJ (300) (12x300)	WC-O-B (500) (16x500)	WC-O (10000)	WC-O-D (50000)
Yellow (WC)	WC-Y-C (100) (10x100)	WC-Y-CJ (100) (50x100)	WC-Y-J (500) (12x500) WC-Y-SJ (200) (12x200)	WC-Y-B (500) (12x500)	WC-Y (10000)	WC-Y-D (35000)
Red (WC)	WC-R-C (100) (10x100)	WC-R-SJ (100) (20x100)	WC-R-J (350) (12x350)	WC-R-B (500) (8x500)	WC-R (5000)	WC-R-D (25000)
High Temp 1 (WC)	—	—	—	WC-HB1-B (1000) (26x1000)	WC-HB1 (10000)	—
High Temp 3 (WC)	—	—	—	WC-HB3-B (500) (16x500)	WC-HB3 (10000)	—

Scan QR code  
for mobile access  
to wire combinations.

